

Shanghai Spreadsun Solar Energy Co., Ltd



TEL : +86 21 65370008 FAX : +86 21 65370078

MOB: +86 13775219101 Email: bruce@spreadsun.com

ADD: No.777, East Changzhi Road, Hongkou District, Shanghai, CHINA

(1) Price list of split pressurized solar water tank

CAPACITY	No copper coil	Single copper coil	Double copper coil
	FOB Shanghai	FOB Shanghai	FOB Shanghai
100L	\$100.00	\$150.00	\$200.00
150L	\$125.00	\$175.00	\$225.00
200L	\$200.00	\$250.00	\$300.00
250L	\$225.00	\$275.00	\$325.00
300L	\$250.00	\$300.00	\$350.00
400L	\$350.00	\$400.00	\$450.00
500L	\$450.00	\$500.00	\$550.00
600L	\$550.00	\$600.00	\$650.00
800L	\$750.00	\$800.00	\$850.00
1000L	\$1,150.00	\$1,300.00	\$1,450.00



(2) Technical data of split pressurized solar water tank

Technical data:								
Tank model	100L	150L	200L	250L	300L	400L	500L	600L
Inner tank diameter(mm)	φ370	φ370	φ470	φ470	φ470	φ600	φ600	φ600

Water tank diameter(mm)	φ470	φ470	φ560	φ560	φ560	φ700	φ700	φ700
Material and thickness of the inner tank(mm)	Stainless steel 316 1.2mm or Enamel 2.5mm	Stainless steel 316 1.2mm or Enamel 2.5mm	Stainless steel 316 1.5mm or Enamel 2.5mm	Stainless steel 316 1.5mm or Enamel 2.5mm	Stainless steel 316 1.8mm or Enamel 2.5mm	Stainless steel 316 2.0mm or Enamel 2.5mm	Stainless steel 316 2.0mm or Enamel 2.5mm	Stainless steel 316 2.0mm or Enamel 2.5mm
Material and thickness of the outer cover(mm)	Galvanized Steel 0.55mm	Galvanized Steel 0.55mm	Galvanized Steel 0.55mm	Galvanized Steel 0.55mm	Galvanized Steel 0.55mm	Galvanized Steel 0.55mm	Galvanized Steel 0.55mm	Galvanized Steel 0.55mm
Insulation thickness(mm)	55mm	55mm	55mm	55mm	55mm	55mm	55mm	55mm
copper coil inlet & outlet diameter	1/2 inch	1/2 inch	1/2 inch	1/2 inch	1/2 inch	1/2 inch	1/2 inch	1/2 inch
inlet & outlet diameter	3/4 inch	3/4 inch	1 inch	1 inch	1 inch	1 inch	1 inch	1 inch
Heat-exchange area of upper coil(m2)	(none)	0.4	0.4	0.4	0.4	0.5	0.5	0.5
Heat-exchange area of bottom coil(m2)	0.6	0.6	0.6	0.7	0.7	0.8	0.8	0.8
Subsidiary heating power	2.5 KW	2.5 KW	2.5 KW	2.5 KW	2.5 KW	3.0 KW	3.0 KW	3.0 KW
Overall dimension(mm)	φ470*1040	φ470*1440	φ560*1250	φ560*1520	φ560*1810	φ700*1540	φ700*1850	φ700*2160
Packing size(mm)	550*550*1120	550*550*1500	640*640*1330	640*640*1580	640*640*1870	780*780*1630	780*780*1950	780*780*2050
Weight (Kg)	34	48	55	60	69	78	100	120