

CONTENTS

www.sunbrighttools.com

SUNBRIGHT
PROFESSIONAL AUTOMOTIVE TOOLS

03



AIR CONDITION SERVICE TOOLS

TUBING TOOLS
COOLING SYSTEM TOOLS

04



BRAKE TOOLS

UNIVERSAL BRAKE REPAIR TOOL, BRAKE OIL SERVICE TOOL
BRAKE CALIPER TOOL

06



ENGINE TOOLS

COMPRESSION TESTERS FUEL SYSTEM RADIATOR PRESSURE
TESTER VALVE TOOL UNIVERSAL ENGINE REPAIR TOOL

12



CHASSIS REPAIR TOOL

BALL JOINT SPRING COMPRESSOR PULLER, BEARING TOOL
WHEEL & TIRE TOOL UNIVERSAL CHASSIS REPAIR TOOL

13



TIMING TOOLS

TIMING LOCKING SET BMW TIMING TOOL KIT BENZ TIMING TOOL KIT
RENAULT TIMING TOOL KIT VOLVO TIMING TOOL KIT VW TIMING TOOL KIT
AUDI TIMING TOOL KIT LAND ROVER TIMING TOOL KIT FORD TIMING TOOL KIT

27



SOCKET & WRENCH & PLIER

SNAP RING PLIER FAN CLUTCH WRENCH
HOSE CLAMP PLIER SOCKET

32



GENERAL TOOLS

TWIN BOLT DISC PAD SPREADER TOOLS DOOR SPRING TOOL
HANDLE CLIP REMOVER COMPOSITE SCRAPER SET

COMPANY PROFILE

Sunbright Tools Co., Ltd. is a leading industrial&trading company specializing in automotive tools including Radiator Pressure Tester, Compression Testers, Timing Tools, Pliers, Puller, Bearing Tool since 2007. We continually develop various kinds of new products according to the market trend and have established our own brand as Sunbright". So far, more than 1,000 kinds of automotive Tools in our product range with excellent quality and competitive price .

Sunbright Tools is located in Jinhua City, Zhejiang province which is near both Ningbo and Shanghai port . We aim at establishing a company image of "reliable quality and excellent service!"

With our elite R&D, design and professional sales team, our company provides consumer-oriented R&D and complete customized solutions to support its industry-leading customers, at the same time we build strategic partnerships with our customer to add value to our products and service that exceed customer expectations.

Sunbright Automotive Tools are popular around the world, our products are exported to over 30 countries in Europe, America, and Japan. We are sure to be the one stop for all your Automotive Repair Tool need!

MY-BCT02

◆MY-BCT02 AIR POWER BRAKE CALIPER WIND BACK TOOL KIT (WITH 15PC BRAKE PADS)



Specification:

- 1: Air Adjusting Lever
- 2: Citroen/XM, Xantia. (F/R)

3: Audi (F). FIAT/Alfa Romeo (F). Ford/Fiesta (F). ISUZU(F). HONDA/Concesto(F). Jaguar/XJ6. XJ40(F/R). BMW/318is. 320i, 325TD, 518i, 525i & 1x, 740i, 850ci, M5.(F). Mercese Benz/190, 200, 300, 420, 560 series (F). Mitsubishi/Colt (F). NISSAN/Mlera. Stanza, Sunny(F). Rover/Austin. Metro, 200 & 400 series, Maestra, Montego(F). TOYOTA/Camry(F). Volvo (F). VW/Passat, Golf GTI (F).

4: FORD Australia/NZ Telstar, Laser (R). MAZDA(R). SAAB 9000 (R). FIAT/Alfa Romeo 1642.0 (R). HONDA/Prelude, CRS 16i, GM/Saturn (R).

5: 3/8" dr. Adapter used with extention bar and ratchet when need to apply more strength to the piston.

6: NISSAN, PRIMERA, VW/Golf IV

7: Audi/80, 90, V8+100, Coupe E(R). Rover/800 ABS. SUBARU L+Z(R). FORD/Sierra ABS, Granada, Scorpio ABS 85(R). NISSAN/Bluebird 1.8 Turbo, Silvia Turbo, Primera 2.0i LS/GS/GSX(R). PEUGEOT/405 1.9Gi, Gri, Sri, Gtxi, MI 16,605 2.0 Sri(R). TOYOTA/Celica, Corolla GT, MR2(R). VW/Golf Gti, Jeta Synchro, Jetta Gti 16v, Passat CL, GL, GT and GT 16v, Corrado 16V scirroca GTX 16V(R).

8: GM most 1-7/8" diameter pistons.
9: GM most 2-1/8" diameter pistons.0: GM most 2-1/2" diameter pistons.
A(Z): Renault/R21, Laguna (Rear Disk).
M: Ford Modeo
N: SAAB, Honda
F(G): Open (Rear disk)
K: Citroen
E: NISSAN Maximas.

MY-BCT05

◆MY-BCT05 BRAKE CALIPER PRESS



Specification:

Works on various single, dual & quad piston calipers.
Centrally distributes force to prevent misalignment of pistons.

360 degree ratchet swing allows access at any angle.

Extended reversing lever allows for easy change from spreading to retracting. Clips between 40mm and 68mm."

MY-BOS10

◆MY-BOS10 BRAKE BLEEDER KIT



Specification:

Brake fluid bleeder works with your air Flush and refill the entire brake system by yourself with this brake fluid bleeder. Comes with:

34 oz Waster Brake Fluid Tank
24 oz New Fluid tank that inserts into your master cylinder with 4 different provided adapters
Size(s) 25/32 in. to 1-7/32 in. diameter (21 To 30mm),

31/32 in. to 1-1/4 in. diameter (24 To 32mm),
1-3/32 in. to 1-15/32 in. (28 To 37mm),
1-1/4 in. to 1-19/32 in. (32 To 41mm)
Air requirement: 90 to 120 PSI, Air inlet: 1/4"-18 NP
Bleeds hydraulic brakes quick and effectively"

MY-BOS05

◆MY-BOS05 BRAKE FLUID BLEEDER EXTRACTOR 300CC-BALL VALVE



Specification:

- 1. Easy to use, save time and power
 - 2. Adjustment: Ball valve manual control
 - 3. Fitment: Brake fluid, coolant, transmission oil, power oil, motorcycle oil, electric vehicle oil, machine oil, mechanical equipment, oil and other useless oil collection
- Material Plastic & Metal
Color White
Volume 300CC
Oil absorbing Rate(max) 1L/min
Working Pressure 0-0.6Mpa(6 Bar)
Tube' s Length 80cm
1 X Pneumatic Pumping Unit (with valve)

MY-BOS12

◆MY-BOS12 PNEUMATIC FLUID EXTRACTOR/



Specification:

Air operated (Pneumatic - non spark) 2 litre capacity
Ease of use - by using vacuum via the bleed nipples there is no requirement for expensive multiple pressure caps. The manual trigger has a locking mechanism to allow hands free use

Automatic cut off
Working pressure: 40-170psi (2.8-12 Bar)
Includes Automatic (hands free) reservoir top up bottle. 1m silicon hose with universal rubber adaptor.

MY-AC47

◆ MY-AC47 FUEL LINE CLAMP & STOPPER KIT 12PCS



Specification:

- 1 x Long Reach Hose Clamp
- 1 x Fuel Pipe Separator
- 2 x Clamp (Metal Fuel Pipe)
- 2 x Clamp (Banjo Fitting)
- 6 x Plugs (2 x 3/16", 2 x 1/4" and 2 x 5/16")

MY-AC54

◆ MY-AC54 A/C COMPRESSOR CLUTCH INSALLER KIT 18PC



Specification:

"Compressor clutch removal tool for GM, Ford, Chrysler, Sanden, Nippondenso, DKS, and Zexel compressors. The kit will remove the clutch hub from all the compressor listed. The kit also contains all the necessary tools to reinstall a clutch hub back onto the compressor.

The kit contains:

- Three eye round clutch plate arbor for Sanden, DKS, & Zexel
- 3 X 1/4" - 20 Hex screws
- 2 X 3/8" - 16 Hex Screws
- 3 X 5 mm - .8 Hex screws
- GM standard thread hub remover / installer
- GM metric thread hub remover / installer
- Chrysler, Nippondenso, & Ford coarse thread hub remover
- DKS hub puller
- Zexel hub puller
- Arbor installer bearings
- Molded carrying case
- NO MANUAL OR INSTRUCTION.
- This kit will not remove a pulley."

MY-AC51

◆ MY-AC51 A/C FLUSH GUN CANISTER CLEAN TOOL KIT HOSE FOR R134A R12 R22 R410A R404A



Specification:

- Model: NVH-399
- Compatible: R134a R12 R22 R410a R404a
- Material: Aluminium alloy bottle, rubber hose, pure copper valve
- Hose Color: Yellow
- Pressure: 0-174psi, 0-12bar
- Volume: 1000mL
- Dimensions:
- Canister: 7.5cmx25.5cm / 3"x10"
- Hose: 90cmx1cm / 35.4"x0.4"
- Vacuum gauge: 4cm / 1.6"
- Canister adapter: 1/4"

MY-AC89

◆ COMPRESSOR CLUTCH REMOVER KIT



Specification:

- Type: Air Conditioning Tools
- Tool Material: Metal
- Color: Black
- Case Material: Plastic
- Professional A/C compressor clutch remover kit
- 2 & 3 Hole puller plates fit most clutches
- Replace clutches found on FS6, C171, 6P & 148 compressors, GM R4 & A6, HR-6, V5 A/C compressors, sedan compressors SD 505, 507, 510, 575, 708 & 709
- Coming with a carry case for easy storage
- Package included:
- 1 Set A/C Compressor Tool

MY-AC53

◆ MY-AC53 STEEL LINE STOPPER KIT 4PCS



Specification:

Use to seal steel lines once disconnected.

- Prevents fluid leaks and contamination during service.
- Use with all automotive fluids.
- Installs in seconds.
- Suitable for Fuel Rails and Lines, Flare Type Steel Brake, Fuel & AC Lines, Banjo fittings on Brake, Power Steering, & Transmission Cooler Lines.

MY-AC954

◆ MY-AC954 SP TOOLS STEEL LINE STOPPER KIT



Specification:

• Use to seal steel lines once disconnected.

- Prevents fluid leaks and contamination during service.
- Use with all automotive fluids.
- Installs in seconds.
- Suitable for Fuel Rails and Lines, Flare Type Steel Brake, Fuel & AC Lines, Banjo fittings on Brake, Power Steering, & Transmission Cooler Lines.

MY-AC04

◆ MY-AC04 A/C CLUTCH HUB CLUTCH INSTALLER KIT



Specification:

A/C service kit contains a complete offering of A/C compressor clutch hub pullers and installers for GM, Ford, Chrysler and Imports. 3700 model Includes a compressor I.D. chart. Comes in a custom molded case. THE CASE MAY BE DAMAGED OR CRACKED DURING SHIPPING. Fits Harrison GM; HT6, HD6, DA-6, HR-6 & V5, A-6 & earlier R4. Nippondenso Ford/Chrysler; A590, C171 & FS-6. For FS-6 w/special 24mm x 2.0 thread. Sanden. York/Tecumseh; HR980. Zexel/Mitsubishi; CH Series"

MY-TUT01

◆ MY-TUT01 HAND FLARING TOOLS SET
3/16-1/2 7PCS



Specification:
Diameter Ø 3/16, 1/4, 5/16, 3/8, 1/2
Application: heating, air-condition and brake systems

MY-UBR13

◆ BRAKE ADJUSTMENT TOOL



Specification:
Quickly adjusts star wheel brakes on most GM vehicles.
Chrome finish resists corrosion.
Offset angle for easy accessibility to confined areas.
Length: 6-3/5"
Arbor installer bearings
Molded carrying case
NO MANUAL OR INSTRUCTION.
This kit will not remove a pulley."

MY-UBR20

◆ BRAKE RETAINER SPRING REMOVER TOOL MY-UBR20



Specification:
Releases the Spring Clip Retainer that Attaches the Rear Brake Cylinder to Backing Plate.
Expands and Holds this Special Retainer so the Brake Cylinder May be Removed.
Insert the Tool Tips into the Retainer Ring and Expand by Turning the Knob.

MY-TUT02

◆ MY-TUT02 TUBING CUTTER & FLARING & SWAGING TOOL KIT



Specification:
FLARES 1/8" , 3/16" , 1/4" , 5/16" , 3/8" , 7/16" , 1/2" , 5/8" AND 3/4" O.D. (1/8" , 1/4" , 3/8" , 1/2" , 5/8" NOM.)

INCLUDES 5 SWAGE ADAPTERS WHICH COVER 3/16" , 1/4" , 5/16" , 3/8" , 1/2" , 5/8" , 3/4" , O.D.(1/8" , 1/4" , 3/8" , 1/2" , 5/8" NOM.)

CUTTER CAPACITY: 1/8" ~ 1 1/8" O.D.
TUBING ALUMINUM ALLOY BODY, CHROME PLATED FINISH WITH A SPARE CUTTING BLADE.

MY-UBR02

◆ BRAKE CALIPER GUIDANCE THREAD REPAIR SET – FOR FORD, VAG, OPEL



Specification:
Brake Caliper Guidance Thread Repair Set.
For repairing the guide pin threads in the wheel bearing housing.

With disassembly of guide pins while changing the brake pads the internal threads are frequently destroyed. The defective threads are repaired professionally and quickly with a heavy duty rustproof high-grade steel thread bush.
Contents: Replacement bushes with copper ring
M9X1.25(packing unit 10 pcs)
special core drill
Special Tap M9X1.25
Hex key 7mm

MY-BCT01

◆ MY-BCT01 BRAKE PISTON WIND-BACK TOOL SET 21 PCS



Specification:
1-1: RIGHT HAND HELIX BOLT
1-2: LEFT HAND HELIX BOLT
2: Citroen/XM, Xantia. (F/R)
3: Audi (F). FIAT/Alfa Romeo (F). Ford/Fiesta (F). ISUZU(F). HONDA/Concesto(F). Jaguar/XJ6,XJ40(F/R).BMW/318is,320i,325T D,518i,525i & 1x,740i,850ci,M5.(F). Mercedes Benz/190, 200, 300, 420, 560 series (F). Mitsubishi/Colt (F). NISSAN/Miera, Stanza, Sunny(F).Rover/Austin, Metro,200 & 400 series, Maestra, Montego(F).TOYOTA/Camry(F). Volvo (F). VW/ Passat, Golf GTI (F).

4: FORD Australia/NZ Telstar, Laser(R). MAZDA(R). SAAB 9000 R). FIAT/Alfa Romeo 1642.0(R).HONDA/Prelude, CRS 16i, GM/Saturn(R).GM/Grand Prix,Lumina.
5: 3/8" dr. Adapter used with extension bar and ratchet when need to apply more strength to the piston.

6: NISSAN, PRIMERA, VW/Golf IV.
7: Audi/80,90,V8+100, Coupe E(R). Rover/800 ABS. SUBARU L+Z(R). FORD/Sierra ABS, Granada, Scorpio ABS 85(R). NISSAN/Bluebird 1.8 Turbo, Silvia Turbo, Primera 2.0i LS/GS/GSX(R). PEUGEOT/405 1.9Gi,Gri, Sri, Gtxi, Mi 16,605 2.0 Sri(R). TOYOTA/Celica, Corolla GT,MR2(R).VW/Golf Gti, Jeta Synchro, Jetta Gti 16v, Passat CL, GL ,GT and GT 16v, Corrado 16V scirocca GTX 16V(R).

8: GM most 1-7/8" diameter pistons.
9: GM most 2-1/8" diameter pistons. (CADI Seville/Eldorad 80-85).
0: GM most 2-1/2" diameter pistons. (Seville/Eldored 79).
A(Z): Renault/R21, Laguna (Rear Disk).
M: Ford Motors Mini Cooper.
N: SAAB. Honda.
F(G): Opel (Rear disk)
E:NISSAN Maximas.
K: Citroen

MY-BCT02

◆MY-BCT02 AIR POWER BRAKE CALIPER WIND BACK TOOL KIT (WITH 15PC BRAKE PADS)



Specification:

- 1: Air Adjusting Lever
- 2: Citroen/XM, Xantia. (F/R)

3: Audi (F). FIAT/Alfa Romeo (F). Ford/Fiesta (F). ISUZU(F). HONDA/Concesto(F). Jaguar/XJ6. XJ40(F/R). BMW/318is. 320i, 325TD, 518i, 525i & 1x, 740i, 850ci, M5.(F). Mercese Benz/190, 200, 300, 420, 560 series (F). Mitsubishi/Colt (F). NISSAN/Mlera. Stanza, Sunny(F). Rover/Austin. Metro, 200 & 400 series, Maestra, Montego(F). TOYOTA/Camry(F). Volvo (F). VW/Passat, Golf GTI (F).

4: FORD Australia/NZ Telstar, Laser (R). MAZDA(R). SAAB 9000 (R). FIAT/Alfa Romeo 1642.0 (R). HONDA/Prelude, CRS 16i, GM/Saturn (R).

5: 3/8" dr. Adapter used with extention bar and ratchet when need to apply more strength to the piston.

6: NISSAN, PRIMERA, VW/Golf IV

7: Audi/80, 90, V8+100, Coupe E(R). Rover/800 ABS. SUBARU L+Z(R). FORD/Sierra ABS, Granada, Scorpio ABS 85(R). NISSAN/Bluebird 1.8 Turbo, Silvia Turbo, Primera 2.0i LS/GS/GSX(R). PEUGEOT/405 1.9Gi, Gri, Sri, Gtxi, MI 16,605 2.0 Sri(R). TOYOTA/Celica, Corolla GT, MR2(R). VW/Golf Gti, Jeta Synchro, Jetta Gti 16v, Passat CL, GL, GT and GT 16v, Corrado 16V scirroca GTX 16V(R).

8: GM most 1-7/8" diameter pistons.
9: GM most 2-1/8" diameter pistons.0: GM most 2-1/2" diameter pistons.
A(Z): Renault/R21, Laguna (Rear Disk).
M: Ford Modeo
N: SAAB, Honda
F(G): Open (Rear disk)
K: Citoren
E: NISSAN Maximas.

MY-BCT05

◆MY-BCT05 BRAKE CALIPER PRESS



Specification:

Works on various single, dual & quad piston calipers.
Centrally distributes force to prevent misalignment of pistons.

360 degree ratchet swing allows access at any angle.

Extended reversing lever allows for easy change from spreading to retracting.
Clips between 40mm and 68mm."

MY-BOS10

◆MY-BOS10 BRAKE BLEEDER KIT



Specification:

Brake fluid bleeder works with your air Flush and refill the entire brake system by yourself with this brake fluid bleeder. Comes with:

34 oz Waster Brake Fluid Tank
24 oz New Fluid tank that inserts into your master cylinder with 4 different provided adapters
Size(s) 25/32 in. to 1-7/32 in. diameter (21 To 30mm),

31/32 in. to 1-1/4 in. diameter (24 To 32mm),
1-3/32 in. to 1-15/32 in. (28 To 37mm),
1-1/4 in. to 1-19/32 in. (32 To 41mm)
Air requirement: 90 to 120 PSI, Air inlet: 1/4"-18 NP
Bleeds hydraulic brakes quick and effectively"

MY-BOS05

◆MY-BOS05 BRAKE FLUID BLEEDER EXTRACTOR 300CC-BALL VALVE



Specification:

- 1. Easy to use, save time and power
 - 2. Adjustment: Ball valve manual control
 - 3. Fitment: Brake fluid, coolant, transmission oil, power oil, motorcycle oil, electric vehicle oil, machine oil, mechanical equipment, oil and other useless oil collection
- Material Plastic & Metal
Color White
Volume 300CC
Oil absorbing Rate(max) 1L/min
Working Pressure 0-0.6Mpa(6 Bar)
Tube' s Length 80cm
1 X Pneumatic Pumping Unit (with valve)

MY-BOS12

◆MY-BOS12 PNEUMATIC FLUID EXTRACTOR/



Specification:

Air operated (Pneumatic - non spark) 2 litre capacity
Ease of use - by using vacuum via the bleed nipples there is no requirement for expensive multiple pressure caps. The manual trigger has a locking mechanism to allow hands free use

Automatic cut off
Working pressure: 40-170psi (2.8-12 Bar)
Includes Automatic (hands free) reservoir top up bottle. 1m silicon hose with universal rubber adaptor.

MY-BOS16

◆ MY-BOS16 HYDRAULIC BLEEDER KIT



Specification:

- Working pressure : 70 - 120 psi.
- Inlet thread size : 1/4 inch NPT.
- Capacity Extracting Tank : 750ml.
- Tube length : 2 m clear tube."

MY-BOS18

◆ MY-BOS18 VACUUM BRAKE BLEEDER KIT 2PCS



"Specification:

- Air operated (Pneumatic - non spark) 2 litre capacity
- Ease of use - by using vacuum via the bleed nipples there is no requirement for expensive multiple pressure caps. The manual trigger has a locking mechanism to allow hands free use"
- Automatic cut off
- Working pressure: 40-170psi (2.8-12 Bar)
- Includes Automatic (hands free) reservoir top up bottle. 1m silicon hose with universal rubber adaptor."

MY-SP27

◆ MY-SP27 SPARK PLUG IGNITION COIL REMOVING AND INSTALLING PULLERS 5PCS



Specification:

- Used to remove and install ignition coils.
- Long shafts with composite T-style handle for control and stability.
- Prevents damage to ignition coils while allowing faster removal."

MY-BOS029

◆ MY-BOS029 HAND HELD BRAKE BLEEDER TESTER SET VACUUM PUMP GAUGE CAR GARAGE TOOL



Specification:

1. DIY brake bleeder tool to minimize mess
 2. Suitable for home and business applications
 3. Designed for all vehicles
 4. Hand pumps with built in vacuum pump
 - (2) 1/4" ID x 23" vacuum hose
 - (2) 1/4" ID x 3" vacuum hose
 - (2) Tapered hose adaptors
 5. T Hose connector
 6. Straight hose connector
 7. Brake bleeder valve adaptors
 8. Universal cup adaptor
 9. 4oz reservoir jar
 10. Jar lids
- Package includes:
- 1 x Vacuum Pump
 - 1 x Reservoir jar
 - 1 x Transfer Lid
 - 1 x Storage Lid
 - 1 x 4 lengths of 1/4" ID tubing
 - 1 x 1 length of 5/32" ID tubing
 - 1 x Automotive Adapter Package
 - 1 x Brake Bleeding Adapter Package
 - 1 x Rubber Cap Adapter
 - 1 x Presented with blow moulded case"

MY-BOS019

◆ MY-BOS019 BRAKE BLEEDER HAND HELD TESTER SET BLEED KIT VACUUM PUMP FLUID BLEEDING KIT



Specifications:

- Accurate vacuum gauge: 0 - 30inHg (76mmHg)
- Package weight: 0.991 kg
- Package Size(L x W x H): 26.00 x 22.00 x 8.00 cm / 10.24 x 8.66 x 3.15 inches
- Package Contents:
- 1 x Brake Bleeder
- 1 x Reservoir Jar
- 7 x Adapter
- 3 x Tube
- 1 x Cup Adapter
- 2 x Plastic Cover
- 1 x English Manual"

MY-SP28

◆ T-HANDLE IGNITION COIL PULLER SET FOR VAG ENGINES 4PCS



Specification:

- Updated set suitable for installation/removal of ignition coils and separating the ht leads from deep-seated park plugs on VAG vehicles.
- Prevents damage to ignition coils while allowing faster removal."

MY-VT29

◆ MY-VT29 DUAL CAM UNIVERSAL VALVE SPRING COMPRESSOR REMOVAL



Specification:

- Plastic coated locking handles to keep valve springs positively compressed during work.
- For use on multi-valve and diesel engines with deep seated valves and on many OHC/OHV petrol/diesel engines.
- Unique dual cam action provides choice of operation either above or below valve.
- Capacity: 55-175mm.
- Throat clearance 10 (250mm).
- Reversible jaw/adaptor."

MY-VT06

◆ MY-VT06 UNIVERSAL VALVE REPAIR KIT



Specification:

KA-5041 Universal overhead cam valve spring compressor
 KA-5029 Valve collet replacer
 KA-5028 Valve holder
 KA-5033 Valve stem seal pliers-straight jaws
 KA-6664 Valve stem seal pliers-30° effect jaws
 14/18mm Compressed air adaptor:
 Compressed air adaptor for 14mm and 18mm spark plug threads-1/4" BSP female airline coupler. Includes 4 adaptors.
 Valve stem installing tool: An interference fit holds the tool allowing it be lowered down into the confined area of the valve guide and thus easily tapped on with hand pressure. There are six sizes: 5mm, 6mm, 7mm, 8mm, 10mm, 11.5mm."

MY-FS01

◆ OIL FILTER CAP WRENCH SET 5PCS



Specification:

24MM CADILLAC 36
 27MM MERCEDES A CLASS
 32MM VAUXHALL/OPEL: ASTRA, CORSA, ZAFIRA
 36MM VAUXHALL/ OPEL: OMEGA DL 16V VECTRA, ZAFIRA 1998 LATER
 BMW: 16V
 FORD: MONDEO 2.0D 16V DURA TORQ ENGINE,
 TRANSIT 2.5 & 2.0 DURA TORQ DIESEL ENGINE
 MERCEDES: 116MB ENGINE VITO CDI
 38MM VAUXHALL/VETRA 2 LITER Diesel engine

MY-VT08

◆ MY-VT08 VALVE SEAL REMOVER AND INSTALLER KIT



Specification:

Knurled Ends On The Adapters Provides Maximum Grip In Oily Conditions
 Remove Stem Oil Seals Squarely And Without Any Damage To The Springs
 Precision Machined Seal Driving Adapters Guide The Seal For Proper Setting
 1 pc Valve Stem Pliers
 2 pc Deep Seal Driving Sockets For Seals
 1 pc 6" Driver Handle
 7 Adapter Sizes: 5mm, 5.5mm, 6mm, 6.6mm, 7mm, 8mm and 3/8"

MY-RPT02

◆ COMPREHENSIVE RADIATOR PRESSURE TESTER & REFILL MASTER KIT 25PC



Specification:

1pcs. Cooling system pump
 1pcs. Vacuum type purge and refill tool
 1pcs. Thermometer
 1pcs. Wrench for adapters

Specification:

1pcs. Radiator cap test connector R123/R124
 1pcs. Radiator cap test connector R123/R125
 1pcs. Universal rubber radiator adapter
 18pcs. Adapter
 Applications: General Motors, Jeep, Peugeot, Subaru, Chrysler, Acura, Mitsubishi, Nissan, Mazda, Toyota, Suzuki, Isuzu, Honda, Lexus, Mercedes Benz (ML class, W123, W126, W124, W163, W164, W168, W201), Volvo, Saab, Citroen, Renault, Fiat, Alfa, VW (Vento, Passat 1996, Golf, Beetle, Sharan, Passat 1997, Passat 2002), Audi (A4, A5, A6), Porsche, BMW (345, E46, E36, E34, E39, E38, E32, E90, E60, E63, E64, E65), Ford Mondeo, Land Rover, Opel, Ford Focus, Jaguar
 Packing - Plastic box"

MY-VT17

◆ MY-VT17 VALVE SPRING COMPRESSOR 3" -6.5" CAPACITY



Specification:

Easy compressor: The ABN Valve Spring Compressor Small Overhead OVH Engine Repair Compressing Tool allows you to effortlessly disassemble and reassemble valves; For correctly fitting, installing, and removing automotive valve springs
 Fits your vehicle: Suitable for small to medium engines with overhead valves; Works with a cylinder head on your workbench or any OVH head removed from the block; 3-inch to 6.5-inch (7.6cm to 16.5cm) capacity with a 6-inch (15.2cm) throat clearance.

Grip comfortably: Molded and cushioned handle that will give you more leverage; Automatic locking and an easy grip handle help you to keep the tool in place and gain slip-free leverage; Less user fatigue and more productivity.

•Easy to use: Close the clamp until the fork-type portion of the tool fits snugly on the spring cap and the screw pivot is on the valve face, then screw in the threaded rod to compress the spring; Automatically locks in place and is simple to release, lift, and compress."

MY-RPT06

◆ MY-RPT06 UNIVERSAL RADIATOR PRESSURE TESTER KIT 28PCS



Specification:

Allows easy testing for leakage in radiator system and quick change of coolant
 Color coded radiator test cap makes it easy to choose the suitable test cap for the job
 Special design of vacuum purge & refill tool connection, test Range 0 - 35 psi.
 One more adaptor than 27pcs kit suitable for domestic and import vehicles."

MY-RPT08

◆ MY-RPT08 RADIATOR PRESSURE TESTER & VACUUM-TYPE COOLING SYSTEM KIT 25PCS



Specification:

- 1.Contents:1 x Gauge: test range 0~2.5 Bar.
1 x blue and 1 x black connector.
17 x radiator tester caps.
5 x radiator purge and refill tool
- 2.Easy work for both testing leakage in radiator system and quick change of coolant in vacuum situation.
- 3.Suitable for universal vehicles.
- 4.Color printed radiator test cap allows easy choosing suitable test cap.
- 5.Special design of vacuum purge & refill tool connection fits nearly all types of radiator opening.
- 6.Application:MB, GM, Jepp, Peugeot, Subaru, Chrysler, Acura, Mitsubishi, Nissan, Mazda, Toyota, Infiniti, Geo, Suzuki, Isuzu, Honda, Lexus, Volvo, Saab, Citroen, Renault, Fiat, Alfa, Mini Cooper, VW, BMW, Ford, Opel, Porsche, Audi....etc."

MY-RPT10

◆ MY-RPT10 VACUUM-TYPE COOLING SYSTEM KIT 27PC



Specification:

- 1.Contents:1 x Gauge: test range 0~2.5 Bar.
1 x blue and 1 x black connector.
17 x radiator tester caps.
5 x radiator purge and refill tool
- 2.Easy work for both testing leakage in radiator system and quick change of coolant in vacuum situation.
- 3.Suitable for universal vehicles.
- 4.Color printed radiator test cap allows easy choosing suitable test cap.
- 5.Special design of vacuum purge & refill tool connection fits nearly all types of radiator opening.
- 6.Application:MB, GM, Jepp, Peugeot, Subaru, Chrysler, Acura, Mitsubishi, Nissan, Mazda, Toyota, Infiniti, Geo, Suzuki, Isuzu, Honda, Lexus, Volvo, Saab, Citroen, Renault, Fiat, Alfa, Mini Cooper, VW, BMW, Ford, Opel, Porsche, Audi....etc"

MY-RPT20

◆ MY-RPT20 VACUUM PRESSURE PUMP BRAKE BLEEDING KIT



Specification:

Professional vacuum/pressure diagnostic tool helps identify a variety of faults on vehicle systems including fuel, ignition, transmission, emission and air conditioning/heating
Set includes reservoirs, hoses and adaptors for bleeding brake and clutch systems
Lightweight aluminium body with simple twist function for pressure and vacuum testing
Large rubber easy to read gauge

MY-RPT44

◆ 14PCS COOLING SYTEM TESTERS



Specification:

Nissan, Mazda, Toyota, Suzuki, Isuzu, Mercedes Benz (ML-class W163, W164), Honda, Lexus, Volvo, Saab, Citroen, Renault, Fiat, Alfa, VW Vento, VW Passat 1996, VW Golf Beatle, VW Sharan, Audi A4, A5, A6, BMW 345, VW Passat 1997-2002, Porsche Cayenne, BMW E32, E34, E36, E38, E39, E46, E90, Ford Mondeo, Land Rover, Opel, Mercedes Benz (C, E & S-class W140, W210, W211, W215, W216, R230)
Packing - Plastic box"

MY-UER06

◆ COOLING SYSTEM VACUUM PURGE&REFILL KIT 4PCS



Specifications:

- Air pressure: - 90psi
- Air consumption: - 12cfm fluid
- Hose length: 900mm
- Air inlet size: 1 / 4BSP
- Package weight: Approx. 1519g
- Product packaging: Plastic box
- 1 X Vacuum purge refill tool
- 1 X Universal radiator adapter
- 1 X Coolant hose
- 1 X English manual "

MY-RPT16

◆ MY-RPT16 COOLING SYSTEM AND RADIATOR CAP PRESSURE TESTER 21 PCS



Specification:

21 pc cooling system pressure testing kit.
14 caps and 2 cap adaptors.
High powered pump.
Easy-to-read dial.
Rubber casing around dial gauge.
Rubber O rings around various caps for air tight seals.
Supplied in blow molded case.

Suitable Makes - Alfa, Audi, BMW, Mercedes-Benz, Chrysler, Citroen, Ford, GM, Honda, Jaguar, Lexus, Mazda, Mitsubishi, Nissan, Opel, Peugeot, Renault, Rover, Saab, Suzuki, Toyota, Volvo and VW.

MY-UER05

◆MY-UER05 VACUUM AND FUEL PUMP TESTER



Specification:

- 1pcs. Gauge 3-1/2" diameter with color-coded scales
- 1pcs. Rubber hose L=600mm, heavy duty
- 4pcs. Brass nozzle
- 2pcs. Plastic nozzle"

MY-UER10

◆MY-UER10 DIESEL INJECTION LEAK BACK MASTER KIT



Specification:

- 1pcs. Plastic cups holder with hook
- 6pcs. Plastic cup 100ml with fuel installation hose
- 6pcs. Graduate with installation sleeve
- 6pcs. Adapter BOSCH
- 6pcs. Adapter SIEMENS
- 6pcs. Adapter DENSO
- 6pcs. Adapter DELPHI"

MY-UER08

◆MY-UER08 MASTER SEAL REMOVER & SOFT HOSE PICK SET 6PCS



Specification:

- Easily remove seals or o-ring or pick soft hoses on vehicle
- Provided with different length and angle fits wide applications
- Angled blade is ideal for removing seals in limited space
- Blade material: SCM 440"

MY-UER12

◆MY-UER12 PISTON RING COMPRESSOR TOOL SET



Specification:

- Band size:
- 2 7/8" to 3 1/8"(73mm to 79mm)
- 3 1/8" to 3 3/8"(79mm to 86mm)
- 3 3/8" to 3 5/8"(86mm to 92mm)
- 3 5/8" to 3 7/8"(92mm to 98mm)
- 3 7/8" to 4 1/8"(98mm to 105mm)
- 4 1/8" to 4 3/8"(105mm to 111mm)
- Tool solutions for most all situations.
- Built to exceed tool standards.
- Tool set for compressing piston rings for cylinder installation.

MY-UER16

◆ COMPLETELY ALTERNATOR REPAIR KIT SET 22PCS



Specification:

- Permits easy removal of freewheel alternator pulley, either on or off the vehicle.
- Allows alternator shaft to be held while the pulley retainer is removed.
- Incorporates a complete range of combination TRX-Star*, spline and hex adaptors to fit most alternators.
- Supplied in carry-case.

- Tools are finished in Chrome Vanadium, Black oxide, and/or polished, Form Fitted Case.

KIT COMPONENTS:

22pc Completely Alternator Repair Kit Tool KIT COMPONENTS:

- 1x T50 T-Profile Bit Socket, 1/2 "drive, 33T-110 mm, fits Mercedes, A-Klasse
- 3 x M10 Spline Bit Sockets, 1/2 "drive, of 33T-110mm (fits BMW, Ford, Mercedes, VAG); 31T-98mm (fits Fiat); 1-10mm (universal fit);
- 1 x T50 T-profile bit, 75mm, universal fit
- 1 x T40 T-profile bit, 75mm, universal fit
- 1 x M8 internal serration XZN Bit, 75mm, universal fit
- 1 x M10 internal serration XZN Bit, 75mm, fits Renault
- 1 x 10mm internal serration XZN Bit, 75mm, universal fit
- 1 x 8mm internal serration XZN Bit, 75mm, universal fit
- 1 x M10 spline bit 14mm HEX, 57mm, fits Renault, BMW, Ford, Mercedes, Porsche, Vauxhall, VAG;
- Special use alternator: 1 x 33T- 22 mm, fits Renault, Mercedes;
- 1 x 33T-17mm, universal fit;
- 1 x 19mm, universal fit;
- 1 x 22mm, universal fit; 1 x 21mm, fits Renault, BMW, Ford, Mercedes, Porsche, Vauxhall,
- VAG; 1 x 4 pin alternator, universal fit;
- 1 x 33T-15mm, fits Ford;
- 1 x 17mm, fits Ford;
- 1 x 38mm, 3 pin, fits Toyota; 1 x H28 x H22mm, fits Porche
- 1 x Bit Adapter for 10mm bits, 1/2 "drive, universal fit
- Removes and installs press-on-type belt drive accessory pulleys
- Works with hand tools or an impact gun.
- Interchangeable components to work on VW, Audi, Seat, Mercedes, Renault, BMW, For Renault, Fiat, etc.
- Kit Weight = 6.7 lbs"

MY-UER07

◆ MY-UER07 UNIVERSAL CLUTCH ALIGNMENT TOOL KIT 11PCS



Specification:
For fast exact clutch plate centering on vehicles with clutch guide bearing. Suitable for most of vehicles.

Contents:
Clutch Aligner Ø20 ~ Ø26.6mm
Clutch Aligner Ø15 ~ Ø19mm
Clutch Aligner Ø23 ~ Ø36mm
Sleeve Ø12, 14, 15, 16, 17, 18, 19, 20mm"

MY-UER55

◆ MY-UER55 OIL SEAL PULLER REMOVER



Specification:
Use to seal steel lines once disconnected. Prevents fluid leaks and contamination during service. Use with all automotive fluids. Suitable for: Fuel rails and lines. Flare type steel brake, fuel & AC lines. Banjo fittings on brake, power steering, transmission cooler lines installs in seconds.

MY-UER17

◆ MY-UER17 ADJUSTABLE SEAL PULLER



Specification:
Designed for oil and grease seals. Two size tips fit nearly all seal applications."

MY-UER15

◆ MY-UER15 MOTORCYCLE BIKE PISTON RING COMPRESSOR TOOL SET 40MM - 85MM



Specification:
Professional tool for commercial or occasional use. Manufactured from chrome vanadium steel for strength and durability. Helps prevent piston ring breakage. Helps to prevent piston ring damage during installation. Ranges from 40mm 85mm and is complete with 4 bands to fit most engines. Time saver. Suitable for 2 or 4 stroke. Comes in a blow molded case for easy storage and transportation."

MY-UER23

◆ MY-UER23 DIESEL INJECTOR SEAT CUTTER SET 17PCS



Specification:
1pcs:19X15mm
1pcs:17X17mm 19X17mm 15.5X15.5mm
15.5X15.5 angle
20.5X17.5 angle 19.5X17mm 17.5X17mm
20X17mm 14X14mm 15.5X250mm cutter hex key-205mm pilot hex-19X170mm
T-handle 19mm"

MY-UER40

◆ MY-UER40 GLOW PLUG DRILLING SET



Specifications:
Item Size: 24.5*10*2cm
Package Size: 20.2*7*30.9cm
Case Color: Red
Tools Color: Silver&Black&Golden
Material: Carbon Steel
Tools Type: Pilot Drills 3.5mm; Dual-size High-tensile Step Drill M8 & M10; Tap: 1/4", M8, M10; Removes Glow Plugs: 8mm and 10mm
Package Included:
1 x Ratchet T-bar
1 x Drill Holding Adaptor
1 x Puller Outer Housing
1 x Force Screw
1 x Force Nut
1 x Top Connection Removal Tool Star Socket
1 x Allen Key
1 x Dual-size High-tensile Step Drill M8 & M10
1 x Pilot Drill Centring Sleeves

MY-UER18

◆ MY-UER18 ADJUSTABLE SEAL PULLER



Specification:
Head Adjusts to 5 Positions. Two hook sizes easily remove most oil and grease seals. Where clearance is a problem, remove the pin to reposition the head. The adjustable head works great on front wheel drive transaxles. Also works on front crankshaft seals without removing the radiator."

MY-UER17

◆ MY-UER17 (RADIATOR) COOLING SYSTEM VACUUM PURGE & REFILL KIT 6PCS



Specification:

Includes: 0 - 76 Cm/HG Vacuum Gauge. Coolant Hose. 3 Adaptors. Instructions. Air Pressure: 90 psi. Air Consumption: 12cfm Fluid Hose Length: 900mm. Air Inlet Size: 1/4" BSP."

MY-UER928

◆ MY-UER928 SERPENTINE BELT TOOL SET 9PCS



Specification:

Used to service automotive serpentine belts equipped with spring-loaded tensioners, without having to remove other components. Multiple size adapters allow service to most automotive serpentine belt applications. Fine ratcheting action and low profile enables work in restricted areas. 7/8" wrench configuration allows for quick and easy change of adapters. Heat-treated and chrome-plated for strength, durability and appearance."

MY-UER116

◆ MY-UER116 STEERING WHEEL LOCK PLATE REMOVER 3PCS



Specification:

Fits all domestic lock plates including tilt and telescoping columns. Total depresses lock plate for easy removal of locking ring. Allow access to steering column for repair work. Comes with standard and metric adapters for most all domestic lock plates."

MY-UER22

◆ MY-UER22 RATCHETING WRENCH SERPENTINE BELT TOOL SET 16PC



"Specification:

- Remove and install belts on serpentine systems using 13mm,14mm,15mm,16mm, and 18mm hex and both 3/8" and 1/2" square drive sizes.
- Two extensions can be bolted on for hard to reach areas. 9" bar with 1/2 square drive fits Chrysler 2.5,3.0 liter and Ford 4.6 liter engines. •23" bar with 3/8" square drive fits Ford 1.9,2.3liter and GM 3.1 liter engines. also includes a GM Fan Clutch Wrench attachment. •Designed to loosen and tighten fan clutch on 1996 and later GM trucks and vans.
- Unique design works with both 10mm and 13mm pulley bolts."

MY-CT16

◆MY-CT16 CYLINDER PRESSURE METER FOR DIESEL TRUCK TU-15A



Specification:

L= 102mm, M10 x 1
L= 113mm, M10 x 1
L= 118mm, M22 x 1.5
L= 119mm, M10 x 1
L= 135mm, M10 x 1.25
Dial gauge L= 340mm, range from 0-1000psi (0 - 70 bar)
Screw adaptor L=160mm
Injector adaptors:
L=63mm, M24 x 2
L=73mm, M22 x 1.5
L=75mm, M20 x 1.5
L=88mm, M24 x 1.5
H fitting
Bleed valve"

MY-UER38

◆ MY-UER38 DIESEL INJECTOR CLEANER SET 7PCS



Specification:

Set of 10 diesel injector seat cutters / centering pilot and T-handle. This set is used to clean and decarbonise injector seats when changing injectors. It helps to avoid blow-back due to poorly seated injectors. Suitable for a wide range of vehicles. 15mm x 19mm Flat Reamer for Universal Injector 17mm x 17mm Flat Reamer for Delphi/Bosch Injectors (BMW/PSA/Renault/Ford.) 17mm x 17mm Angled Reamer 17mm x 19mm Flat Reamer Mercedes Benz CRD 17mm x 21mm Angled Reamer Fiat Iveco r 18mm x 21mm Flat Reamer 20mm x 21mm Flat Reamer Centering Pilot post 15.5 X 225mm Cutter 19mm T Handle 135 x 160m"

MY-CT01

◆ OIL COMBUSTION PRESSURE METER



Specification:

Made of high quality copper, rubber, organic glass, plastic in excellent manufacturing for long time use. Easy to read dual scale gauge. It is able to detect oil pressure in engine. Meter head has shockproof set. Designed with pressure reducing valve and hook for convenience. Easy to operate, include PP outer box. Material: Copper, rubber, organic glass, plastic Meter head: Ø8.9cm Measuring range: 0-140psi Size:45*34*13cm Weight: 4.5kg Package: 1 set of Fuel Injector Injection tester kit"

MY-CT03

◆ **TU-113 OIL COMBUSTION SPARYING PRESSURE METER**



Specification:

- Rubber hose: 3/8" x 3" long
- Short flex hose
- Medium flex hose
- Long flex hose
- 2 Pc hose clamps
- Package Content:
- 1x Pressure gauge: (100 PSI, 0-7 bar)
- 1x Brass fitting: 1/4" barbed x 1/4"-18
- 1x Brass fitting: 1/8" - 27 NPT x 1/4" - 18 NPT
- 1x Rubber hose: 1/4" x 4" long
- 1x Rubber hose: 3/8" x 3" long
- 1x Short flex hose
- 1x Medium flex hose
- 1x Long flex hose
- 2x Pcs hose clamps"

MY-CT08

◆ **MY-CT08 CYLINDER PRESSURE METER**



Specification:

Quickly and accurately check the compression, which can help diagnose worn valves, worn bores, head gaskets etc.

SET INCLUDES THE FOLLOWING

1. 1 x heavy duty gauge 0 20 Bar / 0 ; 290 PSI
2. 4 x thread chasers ; M10 / M12 / M14 and M18
3. 4 x extensions ; M10 / M12 / M14 and M18
4. Selection of spare O rings

Supplied in a blow molded case for easy storage and transportation. "

MY-CT05

◆ **AUTOMATIC WAVE-BOX PRESSURE METER TU-11A**



Specification:

Designed to check engine oil pressure in both cars and trucks.
Easy to read dual scale gauge. Complete with 24 (600mm) of oil proof hose with 1/8NPT.
Also includes 1/4NPT and 3/8NPT adaptors.
Dual gauge readings:0 to 300 psi (0 to 21 bar)
Gauge diameter:2.5"

MY-GT02

◆ **MY-GT02 CARBURETOR SYNCHRONIZER (COMPOUND)**



Specification:

Air flow control is handled by needle and seat valves instead of knobs. This helps to resist the dial indicator "bounce" associated with many other lower quality gauges. Set comes complete with black mold storage case.

This kit lets you synchronise the values of the 4 carburetors as well as adjust/set them.

Composition :

- 4 mano of synchronization with fixed frames (vacuum)
- 4 rubber pipes 8x5x750mm
- 4 Tubes of extension 3.9x52mm and 4 tubes 3.9x122mm
- 8 Tubes of conical type 8x40mm
- 4 Tubes 10x53mm (M6x0.75)
- 4 Tubes 10x60mm (M6x1.0)

Measure Range:

1,positive pressure:0-1kg/cm²;

2,negative pressure:0-70cm/Hg"

MY-CT07

◆ **MY-CT07 LUXURY COMPRESSION TESTER KIT**



Specification:

Practical Cylinder Compression Tester for petrol engines.
Compact design
Cylinder Compression Tester from 0-20 bar or 0-300 psi
Cylinder Compression Tester with 2x Pressure Tubes with rubber nozzles
Convenient Carry Case for Cylinder Compression Tester

The Cylinder Compression Tester measures the piston pressure quick and easily, right underneath the spark plug thread.
Suitable for petrol engine motorcycles and automotive vehicles
Comes with specially designed molded case for storage

Specifications:

Thread sizes

- M18x1.5
- M14x1.25
- M12x1.25
- M10x1.0

Package Dimension (L x W x H): 28.5 cm x 6.5 cm x 22.5 cm

Weight: 1.1 kg

Package Includes:

MY-CT026

◆ **MY-CT026 RAPID TYPE CYLINDER PRESSURE GAUGE**



Specification:

Compression gauge with dual scale, range from 0-300psi (0 - 20 bar)
Screw-in adapters M18 x 1.5, M14 x 1.25, M10 x 1.0, M12 x 1.25
Press-in adapters
Plastic box"

MY-GT12

◆ MY-GT12 UNIVERSAL TWIN CAM LOCKING TIMING TOOL KIT FOR PETROL DIESEL ENGINES AUTOMOTIVE



Specification:
Professional tool for commercial or occasional use.
Designed to lock twin camshafts to timing marks during timing belt replacement. Universa tool as only one tool is needed to do all twin cam.
Fits onto sprockets and extends to lock into sprocket teeth.
Adjustable arms to fit various diameters and tooth pitch.
Suitable for locking between cam and diesel injection pump sprockets.
Suitable for both petrol and diesel engines.
Can also be used to lock a diesel fuel pump to the camshaft sprocket."

MY-WR58

◆ MY-WR58 GEARWRENCH PULLEY HOLDER TOOL KIT



Specification:
GearWrench 3472 Pulley Holder / Fan Clutch Tool Kit

Includes Universal Pulley Holder 3471 plus fan clutch wrenches 3422 & 3136-76.

Used to remove and replace thermostatic fan assemblies while eliminating the need for various size holding.

Item Weight - 5.1 lbs.Applications.
3 pcs Fan Clutch Wrench Kit.
Ford trucks w/2.8L, 2.9L, 3.0L, 4.0L, 4.9L and 5.0L engine."

MY-GT15

◆ MY-GT15 DOOR SPRING TOOL



Specification:
Use with 1/2" wrench or socket.
Safely removes and installs door springs on most GM cars and trucks.
Alloy steel construction."

MY-WR22

◆ MY-WR22 ADJUSTABLE PIN WRENCH



Specification:Adjustable Pin Wrench
Easy twist knob adjustment.
Fits grinder hubs from 3/8"-1-1/16" in size.
Over all size Cushioned grip.

MY-GT16

◆ MY-GT16 DOOR HANDLE CLIP REMOVER 10 IN 1



Specification:
Multipurpose panel beating tool for removing and installing auto trim fittings&fixtures.
Material: Tempered spring steel.
Includes:
1.Headlamp spring tool.
2.Windshield molding clip remover.
3.Door ruber plastic clip remover.
4.Serrated edge for panel seam detail neatening. 5.Molding remover.
6.Windshield wiper wrench.
7.Door rubber metal clip inserter.
8.Door weather strip clip remover.
9.Door handle clip remover.
10.Door trim bezel clip remover. "

MY-GT90

◆ MY-GT90 COMPOSITE SCRAPER SET 4PC



Specification:
Specially made material for taking off auto body parts, removing gaskets and debris from aluminum pa.

Remove decals, emblems and body molding without scratching painted surfaces.

Designed to absorb hammer blows.

Comes with four different sizes - 3/4, 7/8, 1 and 1-1/2-inch.

Handy set for taking decals, batches and other parts without damaging the paint/part"

MY-GT14

◆ MY-GT14 TWIN BOLT DISC PAD SPREADER TOOLS EQUIPMENT HAND TOOLS



Specification:
Used to compress pistons back into calipers when installing new brake pads on any single or dual sliding type caliper.

Swiveling nose pieces reduce the chance of piston cocking.
Fine threaded screws for added pressure."

MY-WR60

◆ MY-WR60 PNEUMATIC FAN CLUTCH WRENCH



Specification:

Tighten or loosen fan clutches effortlessly to change the water pump
Popular size wrenches to fit Ford, GM, VW, BMW, and Chrysler vehicles
17" long driver handle for more clearance
Wrench sizes: 7/8" , 32mm, 36mm, 40mm, 47mm, 1-7/8" , and 2"
All items fit in the included storage case"

MY-WR942

◆ MY-WR942 FAN CLUTCH SPANNER WRENCH SET, 5PCS. 1/2" DRIVE



Specification:

For removing and installing pressed and bolt-on water pump pulleys. use with 1/2" ratchet other square drive for flexibility in tight spaces.
A double-sided tool that fits GM gas engine 2000 and newer, Jeep and Dodge 2000 and newer Except 2009 and newer Hemi.
Works on 2009 and newer Double Hemi.
Fits 2001-2013 GM Duramax diesels.
Works on 2011 and New Ford 6.7L diesels.
Fits all sizes of bolt on water pump pulleys and uses a unique cam design to hold the pulley by trapping one of the bolt heads."

MY-WR61

◆ MY-WR61 CTA TOOLS 1085 AUDI CAMSHAFT HOLDING TOOL 1 PACK



Specification:

For assembly and disassembly of pulleys on Camshaft, vibration and oil pump.
Includes 2 Sets of pins, one with 3-steps for a total of 4 diameters.
Use for mounting and dismounting of the Camshaft, timing belt replacement, testing and adjustment of Camshaft timing, Locking the crankshaft.
Holding arm swivels to adjust pin range from 2cm to 13cm. Tool length is 43cm/17" for extra reach and leverage.
Handle with thick Steel Construction and cushion grip. Comparable to tool T10172."

MY-WR932

◆ MY-WR932 FAN CLUTCH WRENCH SET 10PCS



Specification:

2-1/4" fan pulley holding tools.
3-1/4" fan pulley holding tools.
2-3/8" fan clutch bolt holding tools.
2-1/8" fan clutch pulley holding tools.
3" fan clutch pulley holding tools.
2-13/16" fan hub wrench.
1-7/16" fan clutch nut wrench.
1-7/16" fan clutch wrench.
1-9/16" fan clutch wrench.
1-7/8" left hand clutch nut wrench.
Square drive ends allows attachment of a breaker bar for extra torque.
Blow molded case keeps the tools organized and easy to transport."

MY-WR108

◆ MY-WR108 FORK SEAL DRIVER SET 9PCS



Specification:

Professional kit to cover most diameter of forks.
Split design for easy operation on both conventional and USD (inverted) forks for the installation of forks seals.
Hardened and tempered carbon steel, finished with zinc plating for corrosion resistance.
• Heavy knurled grip gives positive purchase when in use and limits risk of slip if hand are oily.
Limits potential damages to the forks caused by using other methods."

MY-WR940

◆ MY-WR940 FAN CLUTCH WRENCH 3 PCS



Specification:

A nearly universal fan clutch wrench set for use on the most popular applications.
Unique hooked wrench design will hold bolted on water pump pulleys by applying pressure against another bolt.
Double-sided spanner style holding wrench will hold pressed on pulleys on many GM, Jeep and Dodge vehicles.
Double-ended turning wrench will work on 36mm and 47mm / 1-7/8" sizes.
1/2" square drive holes in the tools are for use with a hand ratchet or breaker bar to create a handle and allow extra force to be applied."

MY-WR943

◆ MY-WR943 FAN HUB WRENCH SET 4PCS



Specification:
32mm open end x 270 mm length.
For reaction the visco-cupping drive on BMW and Ford.
36mm open end x 270 mm length.
For reaction the visco-cupping drive on Ford, Opel and GM
41mm open end x 270 mm length.
For twisting the water pump on Opel and GM when tightening the belt on OHC-engines.
46mm open end x 270 mm length.
For twisting the water pump on Opel and GM when tightening the belt on OHC-engines. "

MY-PL05

◆ MY-PL05 ANGLED FLAT BAND HOSE CLAMP PLIERS



Specification:
Keep wire clamps spread open and free both hands.
Finger tip "position lock" makes it easy to replace the lower radiator hose.
45" designed to fit some clamps in deep position.
Keep wire clamps spread open and free both hands.
Finger tip "position lock" makes it easy to replace the lower radiator hose.
Length:8.5"

MY-PL01

◆ MY-PL01 SWIVEL JAW BAND CLIP PLIERS



Specification:
Finger tip "position lock" to keep hose clamps spread open.
Convenient for replacement of lower radiator hose.
Fit most size clamps
PVC dipped handles for improved grip and comfort.
Length:225mm
Special "V" slot and cross slot jaws. "

MY-WR213

◆ UNIVERSAL TWO WAY OIL FILTER WRENCH REMOVAL TOOL FULLY ADJUSTABLE HEAVY DUTY



Specification: Drive: 3/8", 1/2" Sq.
Capacity: Φ65-110mm. Stain chrome finish steel construction with 3/8", 1/2" Sq drive.
Also suitable for use with a 21mm (13/16") spanner. •Claws grip fitter tighter as more torque is applied.

MY-PL04

◆ MY-PL04 HOSE CLAMP PLIERS 9"



Specification:
Keep wire clamps spread open and free both hands.
Finger tip "position lock" makes it easy to replace the lower radiator hose.
Length:9"

MY-PL03

◆ MY-PL03 FLAT BAND CLIP PLIERS



Specification:
Finger tip "position lock" to keep hose clamps spread open. with nickel plant handle.
Convenient for replacement of lower radiator hose.
Fit most size clamps
PVC dipped handles for improved grip and comfort.
Length:225mm
Special "O" slot and "O" slot jaws. "

MY-PL06

◆ MY-PL06 DRAKE OFF ROAD HOSE REMOVER PLIER TOOL FOR CAR



Specification:
Drake Off Road Hose Remover Plier tool for car auto
For easy removal of 5/32 inches to 1/2 inches vacuum and fuel hoses.
Comes in skin-pack.
Works on most flat-band hose clamps. "

MY-PL07

◆ MY-PL07 8.5" CIRCLIP PLIERS SET 2PCS



Specification:
For easy removal and installation of ring type hose clamps.
Swivel type jaws grip at angle to allow access in confined areas.
Includes: 1 pc "V" slot jaw hose clamp pliers and 1 pc cross slot jaw hose clamp pliers. "

MY-PL08

◆MY-PL08 HOSE CLAMP PLIERS SET 5PCS



Specification:

1 x 280mm Flexible ratchet hose clamp with 700mm twin cables.
1 x 200mm Ratchet hose clamp plier with rotating V groove patten jaw blocks.
1 x 200mm Ratchet hose clamp plier with rotating cross groove patten jaw blocks.
1 x 200mm Ratchet hose clamp plier with rotating cup and slot groove patten jaw blocks.
1 x 250mm spring loaded multi-purpose hose and wire calmp pliers with rotating curved interlocking jaws.
A comprehensive set for removing and replacing most types of spring loaded self tightening hose clamps.
Feature: Comprises five of the most common types of pliers with four jaw patterns and a ratchet clamp system. Ratchet mechanism fitted to most of the pliers. PVC dipped handles for operator comfort."

MY-PL11

◆ MY-PL11 BRASS 3/16", 1/4" LINES BRAKE LINE FORMING BENDING TOOL PLIERS



Specification:

Brass 3/16", 1/4" lines Brake Line Forming Bending Tool Pliers. For use on 3/16" and 1/4" brake, AC, and fuel lines.
For use aligning, bending, and adjusting brake and fuel lines, fitting new hard lines, and changing the bend of existing lines.
Constructed from heavy duty forged steel for strength and durability.
Handle grips provide firm hold and comfort. Easily bends tube without damaging or distorting tubing.

MY-PL09

◆ MY-PL09 EXTENDED REACH HOSE CLAMP PLIERS SET 3PC



Specification:

Fully adjustable hose clamp pliers enable the professional technician to access, release tension and remove most constant tension hose clamps, no matter what size. Newly designed superoored enclosed ratchet mechanism for safe operation. Set includes straight 45°&90°angled heads for optimum positioning."

MY-PL12

◆MY-PL12 SIMPLY SILVER - GLOW PLUG CONNECTOR REMOVER STRAIGHT PLIER



Specification:

Designed to remove hard to reach glow plugs connectors, prevents damage. Straight heads for direct access and soft grip handles with thumb restraints for extra pressure. Suitable for diesel engines, Mercedes-Benz, VW, AUDI, SEAT, SKODA, BMW, etc."

MY-PL22

◆MY-PL22 HOSE CLIP PLIERS CV BOOT CLAMP PLIERS



Specification:

For assembly of new stainless steel calm-bands on drive shafts where a torque setting is required. The 3/8" Torque wrench is ideal to provide the drive. Length:250mm."

MY-PL10

◆ MY-PL10 WHEEL BALANCE PLIER



Specification:

Multi-purpose tool. Primary designed for the installation and removal of wheel balance weights. Also includes tools for prising off wheel trims and preparing wheel balance weights."

MY-PL13

◆ MY-PL13 HARPOW ANGLED GLOW PLUG CONNECTOR REMOVER



Specification:

Pliers Diesel Engines. Glow-plug Connector Plier. Special angle designed to remove stubborn and hardly accessible glow plug connectors which installed on the latest generation engines. Applicable :Benz,BMW,VW,Audi etc."

MY-PL15

◆ MY-PL15 ABN UPHOLSTERY TRIM CLIP REMOVAL PLIERS



Specification:

Removes door upholstery and other trim items anchors. 2-Step tip allows easy access to deep under clip heads to prevent slippage. Spring loaded handle for a great leverage."

MY-PL16

◆ MY-PL16 HOSE CLAMP PLIERS SET 7PCS



Specification:
With ear-down device that prevents the release of the cuff closure.
Universal use in axle boots, fuel hoses and radiator hoses.
Requires for the processing of ear clips (system oetiker)
Length 235mm spring band clamps pliers.
Specially made for space-saving spring clamps. Ratchet mechanism for holding the clamp. Especially suitable for new spring clips to VAG fuel lines.
Bowden cable hose clamp pliers.
Allows installation and removal of all flexible, self-locking.
Spring steel band clamps 18 to 54mm. On by bowden also difficult to access suitable.
Length 630mm.
Hose clamps tension tool.
Professional tool for commercial or occasional use. Suitable for compressing spring type hose clamps, particularly useful in confined spaces.
Universal for most vehicles including new VAG clips.
3 way design allows for use on clic, clic R and standard type hose clips.
Suitable for getting into tight spaced and wrongfully positioned clips. Jaw capacity 60mm. Total length of the tool 110mm. Self tensioning spring band clamps and space saving. Clamping range from 6mm to 60mm diameter. Can be used by external hexagon wrench /Allen key 14mm or 1/4 drive ratchet.

MY-PL24

◆ MY-PL24 EAR-TYPE CVJ HOSE CLIP PLIERS



Specification:
Formed steel arms with insulated vinyl handles.
Suitable for ear-type hose clip found on fuel, cooling system and vacuum hoses. Also used for securing CVJ boot clips. "

MY-PL17

◆ MY-PL17 REPLY PULLER



Specification:
Pliers for removing electrical relays on most domestic and import vehicles.
Offset handle and thin tips allow access to relays in confined areas.
Specially designed tip are angled to fit slots or edge of relay cover.
Allows relay to pop free from socket with less chance of damaging relay cover.
Also work on many heavy duty and industrial appliances.

MY-PL20

◆ MY-PL20 CLIC-R TYPE HOSE PLIER COLLAR CLIP SWIVEL DRIVE SHAFTS ANGLE BOOT CLAMP



Specification:
Made from steel and then hardened and tempered for added strength and durability when using this application.
Heavy duty spring loaded pliers for fitting and removing Clic and Clic R hose clips.
Special jaws allows the change from fit to remove simply by turning the pliers over.
Plastic covered handles for comfort and grip when using this application.
Single rivet design."

MY-PL19

◆ MY-PL19 EXHAUST HANGER REMOVAL PLIERS



Specification:
For removal of rubber exhaust system hangers (i.e. tailpipe, exhaust piper and muffler).
Self-locating forcing pin.
Cushioned slip-resistant handles at a 25 degree offset for easy access in restricted areas."

MY-PL21

◆ MY-PL21 EAR TYPE O-CLIP PLIERS CV JOINT BOOT PLIER CRIMPING TOOL EXTRA HEAVY DUTY BERGEN



Specification: Extra Heavy Duty Bergen
For all ear-type clamps.
Application: For AUDI, BMW, CHRYSLER, FORD, GM, HONDA, MAZDA, MERCEDES, NISSAN, OPEL, VAUXHALL, VW ETC.
Designed to use with a 1/2" extension handle or torque wrench."

MY-PL23

◆ MY-PL23 EAR-TYPE CVJ BOOT PLIERS



Specification:
Ear-Type CVJ Boot/Hose Clip Pliers
Formed steel arms with insulated vinyl handles.
Suitable for ear-type hose clip found on fuel, cooling system and vacuum hoses. Also used for securing CVJ boot clips. "

MY-PL28

◆ MY-PL28 HEAVY DUTY SPARK PLUG BOOT PLIER



Specification:
45° offset vinyl coated jaws to assure complete coverage of all contact areas. Non-slip, vinyl coated handles. Use only on automotive type ignition systems."

MY-PL26

◆ MY-PL26 CV JOINT BOOT CLAMPS PLIERS BANDING TOOLS KIT SET 2PCS



Specification:
Heavy Duty.
Comfortable double dipped handles.
Hardened steel.
CV boot clamp installer.
To be used with any banding up to 10mm in width
CV Boot.
Hose Clamp Pliers Ear Type .
Crimps and flattens clamps on ear type CV joint boot clamps .
For installing CV Clamps.
Standard banding tool for CV Joint Boots."

MY-PL27

◆ MY-PL27 CV JOINT CLAMP PLIER



Specification:
Essential tool for specialised clips.
Locking function.
For use on turbo boost hose clips fitted to: Volkswagen Passat 2.0 Tdi(05)/Touran/Golf V/Audi A3/Touran/Golf V/Audi A3/Skoda Octavia."

MY-PL34

◆ MY-PL34 SHORT NECK VALVE STEM SEAL PLIERS



Specification:
Steel long stem aids removal and installation of valve stem seals on 16 and 24 valve OHC engines.
Serrated tips aid grip.
Especially suited to stubborn seals.
Length:235mm."

MY-PL29

◆ MY-PL29 HEAVY-DUTY SPARK PLUG WIRE BOOT PLIERS



Specification:
Offers Easy and Safe Way to Remove Spark Plugs Even While Engine Runs.
Featuring Ruggedly Crafted Handles and Jaws.
Insulated Design Offers Protection from Shock.
Jaws Engineered with Small Indentations Allowing for Gripping Bare Terminals.
Overall Length of 8-Inches (20-Centimeters)."

MY-PL30

◆ MY-PL30 FUEL FEED PIPE PLIERS REMOVAL HOSE LINE CLIP CLAMP MERCEDES BMW AUDI VW GM



Specification:
Removal and replacement of the fuel line for Mercedes, VW, Audi, Fiat, GM, Opel.
Tool overall length is 9.0" (233mm).
Tool Tip is 0.185" (4.6mm).
Padded handles for additional comfort.
Durable commercial use tool."

MY-PL37

◆ MY-PL37 FUEL LINE DISCONNECTION



Specification:
Suitable for Audi, Citroen, Mercedes, Vauxhall, Opel, Peugeot Renault, Volkswagen, ETC.
Without this tool the clips can be released but not re-fitted."

MY-PL47

◆ MY-PL47 REMOTE ACTION HOSE CLIP SET



Specification:
For replacement of fuel oil and water hose.
Clamp with flexible 630 wire.
Convenient for working hidden areas and long distance."

MY-PL31

◆ MY-PL31 FUEL FEED PIPE PLIERS



Specification:
Designed for the removal of connectors on in-line fuel filter.
For Alfa Romeo, Audi, Volkswagen, Lancia & Volvo.
moulded handles for easy grip.
Great time saver.
Aluminium alloy."

MY-PL32

◆ MY-PL32 MULTI-PURPOSE HOSE&WIRE PLIERS 8.5"



Specification:
Ideal for disassembly vacuum hose, radiator hose, fuel hose, spark plug lead wire.
Capacity: 1/4" to 3/4" O.D.
Remove engine 1/4" air pipe.
Remove engine intake air pipe.
Remove spark plug lead.
Remove cooling water pipe.
Length: 8.5".

MY-PL33

◆ MY-PL33 MULTI-PURPOSE HOSE&WIRE PLIERS 10"



Specification:
Ideal for disassembly vacuum hose, radiator hose, fuel hose, spark plug lead wire.
Capacity: 1/4" to 3/4" O.D.
Remove engine 1/4" air pipe.
Remove engine intake air pipe.
Remove spark plug lead.
Remove cooling water pipe.
Length: 10".

MY-PL35

◆ MY-PL35 LONG NECK VALVE STEM SEAL PLIERS



Specification:
Long neck designed to reach into confined area of the seal to grip it for removal. Gripping serratio allows them to grasp both original equipment & after market seals. Regardless of the configuration. Production of high quality steel. Packing & shipping International standard packing ensures your products arrive safely."

MY-PL36

◆ MY-PL36 FUEL LINE DISCONNECTION



Specification:
Hose clamps pliers for 3-terminal ends. Facilitates the disassembly and assembly of small self-tightening hose clamps with flat 3-terminal ends. For example, fuel lines and cooling and washing water hose hardeded, non-warping burnished jaws. Self-opening by spring mechanism. Maximum opening 24mm. Total length 190mm. Chrome handles. Suitable for various models of Audi, Seat, Skoda, Toyota and Volkswagen."

MY-PL45

◆ MY-PL45 REMOTE ACTION HOSE CLIP TOOL FLEXIBLE HOSE CLAMP PLIERS



Specification: Clamp: metal, plastic self tensioned clips. Clamp opening range: 0-50mm. Clamping width: 12mm. Slide width complete: 20mm. Slide length: 96mm. Wire length: 630mm. Pliers length: 230mm. Pliers have locking mechanism to hold clamp in the open position. 630mm/24" long wire, users can reach, remove, and lock clamp into open position more flexible. Making removal and installation of clamp easier, specially designed for easy hose replacement. Suitable for metal, plastic metal and self tightening ratcheting hose clamps. Suitable for hose clamp 18-54mm diameter.

MY-PL39

◆ MY-PL39 HOSE PINCH-OFF PLIERS 10"



Specification:
Tightly when you are servicing various engine components. No need to drain system when changing thermostats-save coolant-save time. Jaws swivel for parallel clamping. Locking ratchet provide tight grip in just about any position. Can also be used to pinch-off many other hoses. Don't use on wire reinforced radiator hose. Length: 10".

MY-PL43

◆ MY-PL43 LONG REACH HOSE CLIP PLIER



Specification:
Flexible shaft length: 500mm. Reinforced long reach tool designed to get to awkwardly positioned tag type hose clips. Flexible cable and compact head help operation in confined space. Features ratchet action for close control."

MY-PL46

◆ MY-PL46 REMOTE ACTION HOSE CLIP TOOL



Specification:
For replacement of fuel, oil and water hose with Clip-R hose clamp. Hose clamp with flexible 630mm wire. Convenient for working hidden areas and long distance."

MY-PL41

◆ MY-PL41 HOSE PINCH-OFF PLIERS
3PCS



Specification:
Tightly when you are servicing various engine components.
No need to drain system when changing thermostats-save coolant-save time.
Jaws swivel for parallel clamping.
Locking ratchet provide tight grip in just about any position.
Can also be used to pinch-off many other hoses.
Don't use on wire reinforced radiator hose.
Length:8",10",12".

MY-PL44

◆ MY-PL44 UNIVERSAL HOSE CLAMP PLIERS



Specification:
Pistol grip for easy use.
Long reach hose clamp pliers with wire flexible wire shaft.
Easy to use in normally inaccessible areas and for extra reach for use on re-usable spring band clamps.
For the removal and locking of clamps into open position.
Suitable for metal, plastic metal and shlf tightening tensioned hose clamps with diameters of 18mm-54mm.
Hose clamps 18-54mm"

MY-PL53

◆ MY-PL53 HOSE CLAMP PLIERS



Specification:
Suitable for progressively adjustable clamps.
Installed on axle boots on VAG, Mercedes and Toyota."

MY-PL42

◆ MY-PL42 HEAVY DUTY HOSE CLAMP PLIERS FLEXIBLE EXTRA LONG REACH HOSE CLIP PLIER



Specification:
Flexible shaft length:500mm.
Reinforced long reach tool designed to get to awkwardly positioned tag type hose clips.
Flexible cable and compact head help operation in confined space.
Features ratchet action for close control."

MY-PL49

◆ MY-PL49 VAG LONG REACH HOSE CLAMP PLIERS



Specification:
Professional tool for commercial or occasional use.
Suitable for the removal and locking of clamps into open positions.
Suitable to fit and operate on the new hose clamps fitted to all Volkswagen and Golf vehicles.
Total length of the wire 360mm so perfect for access into those hard to reach awkward areas.
Comes with flexible wire shaft.
Allows the removal of plastic or metal self tightening hose clamps.
Pliers can be locked giving hands free operation.
Rubber ergonomic handles for comfort and grip when using this appliaction VAT receipt included."

MY-PL50

◆ MY-PL50 TRANSMISSION AND POWER STEERING OIL COOLER LINE PLIERS BMW



Specification:
BMW:1 Series:E81,E82,E87.
3 Series:E46,E90.
5 Series:E60.
6 Series:E63.
7 Series:E65.
X3:E83.
X5:E53,E70.
Z4:E85.
Mini:R50,R52,R53

MY-PL54

◆ MY-PL54 PISTON RING INSTALLER



Specification:
Tapered jaws to remove and install most passenger car and light truck rings from 3/64" to 1/4" (1.2 - 6.3mm).
Skin-packed."

MY-PL52

◆ MY-PL52 EARLESS TYPE CVJ BOOT/HOSE CLIP PLIERS



Specification:
Steel jaws with formed handles for extra comfort.
Suitable for all earless type CVJ boot clamps.
Length:240mm."

MY-PL48

◆MY-PL48 VAG LONG REACH HOSE CLAMP PLIERS



Specification:
Professional tool for commercial or occasional use.
Suitable for the removal and locking of clamps into open positions.
Suitable to fit and operate on the new hose clamps fitted to all Volkswagen and Golf vehicles.
Total length of the wire 360mm so perfect for access into those hard to reach awkward areas.
Comes with flexible wire shaft.
Allows the removal of plastic or metal self tightening hose clamps.
Pliers can be locked giving hands free operation.
Rubber ergonomic handles for comfort and grip when using this application VAT receipt included."

MY-PL55

◆MY-PL55 PISTON RING QUICK INSTALLER REMOVER ENGINE PLIERS SUIT 4" 50MM-100MM



Specification:
This plier suit 50mm-100mm.
These piston ring pliers make it easy to remove and replace piston rings.
Even spreader action prevents ring breakage and prevents piston wall scoring.
Universal design can be used on most vehicles.
Applies pressure evenly to prevent ring breakage."

MY-PL56

◆MY-PL56 PISTON RING QUICK INSTALLER REMOVER ENGINE PLIERS SUIT 6" 80MM-120MM



Specification:
This plier suit 80mm-120mm.
These piston ring pliers make it easy to remove and replace piston rings.
Even spreader action prevents ring breakage and prevents piston wall scoring.
Universal design can be used on most vehicles.
Applies pressure evenly to prevent ring breakage"

MY-PL57

◆MY-PL57 PISTON RING QUICK INSTALLER REMOVER ENGINE PLIERS SUIT 8" 120MM-160MM



Specification:
This plier suit 120mm-160mm.
These piston ring pliers make it easy to remove and replace piston rings.
Even spreader action prevents ring breakage and prevents piston wall scoring.
Universal design can be used on most vehicles.
Applies pressure evenly to prevent ring breakage."

MY-PL67

◆MY-PL67 SWIVEL JAW SPRING WIRE CLIP PLIERS



Specification:Swivel Jaw Spring Wire Clip Pliers
Design for the soft removal and installation of relays commonly found on modern vehicles.

MY-PL63

◆MY-PL63 CLIC HOSE CLAMP PLIERS



Specification:
Used to loosen and remove a wide variety of automotive hose clamps
Long, flexible cable allows for use in hard-to-reach areas
Spring-loaded ratchet has multiple stops for less strain on the user
Over all length: 7-Inch

MY-PL70

◆MY-PL70TUBE BENDING PLIERS FOR METAL PIPE



Specification:
Pipe bending pliers.
For bending of copper, aluminium, and steel pipes with diameters of 4,6,8,10mm 2 replaceable bending rollers on each of which 180° for 4 and 6mm, and 8mm and 10mm are formed.
Tool in the highest-quality execution.
For durability in daily use in the workshop."

MY-PL73

◆MY-PL73 EXHAUST PIPE CLAMP PLIERS



Specification:
Exhaust pipe clamp removal pliers without need to remove the screw off of the clamp.
50mm jaws.
Length 300mm. "

MY-PL74

◆MY-PL74 MULTI-DIRECTION SPRING LOADED HOSE CLAMP PLIERS 9-CIRCLE



Specification:
Large-than-normal(16mm)jaw heads make it easier to remove hose clamps. Cross-shaped jaws enhance plier's ability to grip objects provide multi-directional operation,suitable for working in limited spaces."

MY-PL51

◆MY-PL51 FUEL LINE DISCONNECT PLIER SET 3PCS



Specification:
3pcs Fuel Line Disconnect Set.
1/4 inch 5/16 inch diameter 8mm Ford-Mercury Dodge-Chrysler Renault.
3/8 inch diameter 10mm Ford-Mercury Dodge-Chrysler Renault.
G.M. Chevrolet Buick-Pontiac Renault/Fiat Ford/Opel.
Design for uncoupling quick release fittings on fuel line to most of the cars."

MY-PL66

◆MY-PL66 RELAY REMOVAL PLIER



Specification:
Designed for the soft removal and installation of relays commonly found on modern vehicles.

MY-PL77

◆MY-PL77 BRAKE SHOE SPREADER PLIERS



Specification:
Long reach tool designed to get to awkwardly positioned tag type hose clips. Flexible cable and compact head help operation in confined space. Features ratchet action and vinyl dipped handles for comfort and close control. Flexible shaft length:630mm."

MY-PL62

◆MY-PL62 TURBO BOOST HOSE CLIP PLIERS



Specification:
Essential tool for specialised clips. Locking function. For use on turbo boost hose clips fitted to:Volkswagen Passat 2.0 Tdi(05)/Touran/Golf V/Audi A3/Touran/Golf V/Audi A3/Skoda Octavia."

MY-PL72

◆MY-PL72 FUEL LINE DISCONNECT PLIER



Specification:
For undoing quick release connections on fuel feed pipe lines on many vehicles including Opel/Vauxhall,Flat,Voldswagen and PSA. Disconnect pilers for fuel lines on many vehicles. Composite handles. Spring loaded. Time saver."

MY-PL60

◆MY-PL60 PUSH PIN PLIERS SET 2PCS



Specification:
30Degree and 80Degree Offset Push Pin Pliers
Anchors Common on Honda, Toyota, GM, Ford, Chrysler and many other late model vehicles. Specially Designed for Removal of Push Pins With Center Lockin Pin. Quickly Removes Plastic Anchors That Have Center Pins Without Damage to Pins or Anchor. Double Cushion Grip Handle."

MY-PL68

◆MY-PL68 WIDE JAW HOSE CLAMP PLIERS



Specification:
Hose cLamp plier 0-38mm x 240mm long. Jaw charom molybdenum-handle carbon steel nickel plated finish&electro deposited coating. Suitable for a variety of ring type or flat band hose clips/clamp. Special waffle shape of jaws securely reaches,grabs,removes or locks hose clamp in place. Patented Product."

MY-PL605

◆MY-PL605 AMERICAN TYPE CIRCLIP PLIER FOR BOTH INTERANAL AND EXTERNAL



American Type Circlip Plier For Both Interanal And External

MY-PL69

◆MY-PL69 HEAVY DUTY RATCHETING SEAL CLAMP PLIERS



Specification:
Ratcheting action provides maximum leverage for making secure high-pressure connections.
Use with 1/4" to 1" clamp sizes.
Numerous applications including fuel lines A/C lines.
Transmission lines and CV boot axles.
Heavy duty construction for long lasting performance."

MY-PL602

◆MY-PL602 RETAINING CIRCLIP PLIERS 4-IN 1



Specification:
To open external snap rings,position jaws on upper pins through upper holes and replace pin.
To open internal snap rings,position jaws on upper pins through upper holes and replace pin.
Use 45° jaws to reach into tight place to install or remove snap rings.
Can be used on 3/8" to 2" internal and external snap rings features interchangeable straight,45° and 90° heads high carbon steel jaws with black finish.

MY-PL604

◆MY-PL604SNAP RING PLIERS SET 2 IN 1



2 In 1 Snap Ring Pliers Set

MY-PL600

◆MY-PL600 SNAP RING PLIERS SET 3 IN 1



Specification:
To open external snap rings,position jaws on upper pins through upper holes and replace pin.

To open internal snap rings,position jaws on upper pins through upper holes and replace pin.

Use 45° jaws to reach into tight place to install or remove snap rings.

Can be used on 3/8" to 2" internal and external snap rings features interchangeable straight,45° and 90° heads high carbon steel jaws with black finish.

MY-PL603

◆MY-PL603 CIRCLIP PLIERS 4 IN 1



Specification:
To open external snap rings,position jaws on upper pins through upper holes and replace pin.

To open internal snap rings,position jaws on upper pins through upper holes and replace pin.

Use 45° jaws to reach into tight place to install or remove snap rings.

Can be used on 3/8" to 2" internal and external snap rings features interchangeable straight,45° and 90° heads high carbon steel jaws with black finish.

MY-PL601

◆MY-PL601 SNAP RING PLIERS SET WITH 4 REMOVABLE JAWS



Specification:
To open external snap rings,position jaws on upper pins through upper holes and replace pin.
To open internal snap rings,position jaws on upper pins through upper holes and replace pin.
Use 45° jaws to reach into tight place to install or remove snap rings.
Can be used on 3/8" to 2" internal and external snap rings features interchangeable straight,45° and 90° heads high carbon steel jaws with black finish.

MY-PL606

◆MY-PL606 LOCK-RING PLIERS - STRAIGHT TIP



Specification:
Spread snap lock rings on brakes,transmissions,pedal shafts,clutch shafts.
Jaws have deep serrations on the outside of tip to help lock rings securely.
Spreading:3.5-28mm.
Total length:225mm. "

MY-PL607

◆MY-PL607 MINI SNAP RING PLIER SET 4PCS



Specification:
Internal and external pliers in straight and bent profiles.
Manufactured from high carbon steel with spring loaded action and non-slip PVC grips.
Tip diameter1.2mm.
Suitable for 10-22mm circlips.

MY-PL608

◆ MY-PL608 INTERNAL/EXTERNAL SNAP RING PLIERS



Specification:
List:

1-pliers handle.
4-Interchangeable tips sets
40°(1set),90°(1set)and180° (2sets).
Works with internal or external snap rings.
Easily convert between internal and external applications by squeezing handle and switching the tab.

MY-PL609

◆ 2-PC. INTERNAL/EXTERNAL TIP SNAP RING PLIERS SET



Specification:

Include 1 pc external snap ring plier and 1 pc internal snap ring plier.
For removing and installing external and internal snap rings.
Straight 45° and 90° angle tips are included in a clear plastic storage box.
Comfortable grip handles.

MY-PL618

◆ MY-PL618 AMERICAN TYPE CIRCLIP PLIER 5PCS



Specification:

List:
straight 200mm,150mm*2,angle 90°180mm,135mm.
Made from high carbon steel with heat-treatment and blackened finish.
Pliers can be reversed for internal and external use.
Selection of straight and angled tip.
PVC dipped handles.
Supplied in a storage case.

MY-PL617

◆ MY-PL617 CIRCLIP PLIER SET 4PCS



Specification:

List:
straight 200mm,150mm,angle 90°180mm,135mm.
Made from high carbon steel with heat-treatment and blackened finish.
Pliers can be reversed for internal and external use.
Selection of straight and angled tip.
PVC dipped handles.

MY-PL610

◆ MY-PL610 AMERICAN TYPE CIRCLIP PLIER



Specification:

List:
straight 200mm,150mm*2,angle 90°180mm,135mm.
Made from high carbon steel with heat-treatment and blackened finish.
Pliers can be reversed for internal and external use.
Selection of straight and angled tip.
PVC dipped handles.
Supplied in a storage case.

MY-PL622

◆ MY-PL622 WHEEL BEARING LOCK RING PLIERS



Specification:

Designed for the removal/installation of the wheel bearing circlip on Citroen, Peugeot, Renault and Toyota vehicles. Features specially designed tips for eyeless circlips, spring loaded jaws and vinyl dipped handles.
Applications:
Citroen:C1,1.0 Petrol,1.4 Hdi(05-15)
Peugeot:107,1.0 Petrol,1.4Hdi(05-15)
Renault:Clio,Mk2.20 16V Spot(98-05)
Toyota:Aygo,1.0 Petrol,1.4Hdi(05-15)

MY-PL704

◆ MY-PL704 SNAP RING PLIER SET 11PC MECHANIC PRO CIRCLIPS W



Specification: •Heat treated steel construction with blackened finished for strength and resistance to corrosion.
All circlip pliers feature reversible joints enabling use for either external or internal circlips.
Fitted with comfortable vinyl grips.
Set include two 125mm picks for hard-to reach or dropped clips.
Supplied in a carry-case:
5-1/2" 140mm bent tip plier,0.038" tips 1mm.
6" 150mm straight tip plier,0.038" tips 1mm.
5-1/2" 140mm bent tip plier,0.047" tips 1.2mm.
6" 150mm straight tip plier,0.047" tips 1.2mm.
7-1/2" 190mm bent tip plier,0.070" tips 1.8mm.
8" 200mm straight tip plier, 0.070" tips 1.8mm.
8-1/2" 215mm bent tip plier,0.090" tips 2.3mm.
•9" 230mm straight tip plier,0.090" tips 2.3mm.
•5" 125mm Hook tool.

MY-PL619

◆ MY-PL619 ENDED CIRCLIP PLIERS - SNAP RING PLIER SET INTERNAL & EXTERNAL 2PCS DOUBLE



Specification:
Make removing and installing snap rings fast and easy.
Work on both internal and external style snap rings.
Snap ring fits into grooves, providing a shoulder for holding components in place. Release easily when rings are in position.

MY-PL623

◆ MY-PL623 INTERNAL SNAP CIRCLIP PLIERS LONG GRIP TIP BENT CALLIPERS 90 DEGREE



Specification:
Configuration: Internal (Long).
Non slip handle.
High strength carbon-steel.
Force lifetime warranty.
Industrial quality.

MY-PL800

◆ MY-PL800 STRAIGHT HOSE CLIP CLAMP PLIERS CORBIN TYPE SWIVEL JAW SPRING WIRE CLIPS 8.5"



Specification:
Length :225mm.
Suitable for removal of tag and wire type hose clips.
Features ratchet locking mechanism for easy use on lower radiator hoses.
Swivel jaws allow use where access is confined.
PVC dipped handles for improved grip and comfort."

MY-PL620

◆ MY-PL620 AMERICAN TYPE CIRCLIP PLIER 5PCS



Specification:
straight 200mm,150mmx2,angle 90°180mm,135mm.
Made from high carbon steel with heat-treatment and blackened finish. Pliers can be reversed for internal and external use.
Selection of straight and angled tip. PVC dipped handles.
Supplied in a storage case.

MY-PL700

◆ MY-PL700 CIRCLIP PLIERS KIT SNAP RING PLIERS 10" 2PCS



Specification:
Offset tip make it easier to install and remove circlips.
Removable and replaceable tips have a spring ratchet locking mechanism to hold circlips securely against tension.
Contents:1PC 10" internal circlip plier.1pc 10" external circlip pliers.16pcs replacement tips 2 each of 108"(2.75mm black finish)and 0.120"(3mm)(0°, 15°, 45°, 90° nickel plant) Length:265mm,Maximum spread:50mm"

MY-PL807

◆ MY-PL807 EXHAUST PIPE CLAMP PLIERS



MY-PL705

◆ MY-PL705 CIRCLIP PLIER SET 12PCS



Specification:
Heat treated steel construction with blackened finished for strength and resistance to corrosion.
All circlip pliers feature reversible joints enabling use for either external or internal circlips.
Fitted with comfortable vinyl grips.
Supplied in a carry-case:
6" tip pliers,0.038" tips(0°,45°,90°)
6" tip pliers,0.047" tips(0°,45°,90°)
8" tip pliers,0.070" tips(0°,45°,90°)
9" tip pliers,0.090" tips(0°,45°,90°)

MY-PL713

◆ MY-PL713 CIRCLIP PLIER SET 10" 2PCS



Specification:
Offset tip make it easier to install and remove circlips.
Removable and replaceable tips have a spring ratchet locking mechanism to hold circlips securely against tension.
Contents:1PC 10" internal circlip plier.1pc 10" external circlip pliers.16pcs replacement tips 2 each of 108"(2.75mm black finish)and 0.120"(3mm)(0°, 15°, 45°, 90° nickel plant) Length:265mm,Maximum spread:50mm

Specification:
Opening exhaust hose clamps quickly and easily.
Ideal for citroen,peugeot and renault exhaust clamps.also suitable for prizing open any type of clamp or clip secured with nut and bolt.
Comfort grip handles with self locking mechanism aid working in spring clamps."

MY-PL809

◆MY-PL809 FLAT BAND HOSE CLAMP PLIERS



Specification:
Adjustable jaws fit all clamp sizes for easy removal and installation.
Tips screw in and out to fit all clamp sizes.
Ratcheting lock mechanism holds the clamp in an open position for easy removal and installation.
Tips can be switched to accommodate different applications.
Offset jaws allow access in hard-to-reach areas."

MY-PL909

◆MY-PL909 HOSE PINCH-OFF PLIERS 3PCS



Specification:
For pinching off rubber hoses e.g. brake, fuel and coolant hoses.
Approx 90° angle.
Suitable for tubes Φ 15 and Φ 24mm
Fiberglass composite material.

MY-PL1034

◆MY-PL1034 LONG REACH PLIER DOUBLE X



Specification:
Size: 11"
Material: CRV with plastic handle.
Packing: blister card, double blister card, bulk, gift box.
TUV GS, Reach Approval.
Finished: chrome, satin, full polished.

MY-PL816

◆MY-PL816 CLIP REMOVAL PLIERS



Specification:
Grips the stem of the clip, not the head, so clips don't break.
Lever action for faster, easier removal.
Works on trim pads, hood insulation, etc.

MY-PL901

◆MY-PL901 HOSE PINCH-OFF PLIERS 3PCS



Specification:
Made from heat resistant nylon.
Rounded jaw edges prevent damage to internal hose reinforcement.
Features locking mechanism for simple one-handed use.
Suitable for brake, coolant, fuel and vacuum hoses.
Size: 160mm, 190mm, 260mm."

MY-PL4064

◆MY-PL4064 JOINTED LONG-REACH LARGE GRIPPER PLIERS 13" DOUBLE



Specification:
This 3 piece 13 inches ring nose pliers set is great for pulling spark plug wires and hoses.
The set includes 1/4 inch diameter ring nose pliers, 1/2 inch diameter ring nose pliers and 3/4 inch diameter ring nose pliers.
Super Grip™ handle.
70° Bend.
Perfectly matched tips with diamond cut serration
Full-polish professional finish."

MY-PL714

◆MY-PL714 SNAP RING PLIER SET 16" 2PCS



Specification:
Offset tip make it easier to install and remove circlips.
Removable and replaceable tips have a spring ratchet locking mechanism to hold circlips securely against tension.
Contents: 1PC 16" internal circlip plier. 1pc 16" external circlip pliers. 12pcs replacement tips 4 each of 0.108" (0° black finish) and 2 each of 0.108" (0°, 15°, 45°, 90° black finish)
Length: 400mm, Maximum spread: 85mm "

MY-PL808

◆MY-PL808 CURVED HOSE CLAMP PLIERS 11"



Specification:
To open external snap rings, position jaws on upper pins through upper holes and replace pin.
To open internal snap rings, position jaws on upper pins through upper holes and replace pin.
Use 45° jaws to reach into tight place to install or remove snap rings.

MY-SO02

◆MY-SO02 AXLE NUT SOCKET SET 9 PCS



Specification:
SOCKET SIZES: Shankly's cv axle socket set contains 29mm, 30mm, 31mm, 32mm, 33mm, 34mm, 35mm, 36mm and 38mm sockets. Useful sockets for many type of axle nut jobs.

MY-PL2034

◆ MY-PL2034 MULTIFUNCTION MIG WELDING PLIERS 8"



Specification:
Specially-designed nose for efficient removal of welding spatter.
Induction-hardened cutting edge stays sharp longer.
Multiple jaws for drawing out wire and removing of installing tips and nozzles.
Hammer designed for light welding gun maintenance.
Spring-loaded with dipped grips for superior comfort and ease of use."

MY-PL4074

◆ MY-PL4074 JOINT PISTOL GRIP DUCKBILL PLIER 13" DOUBLE



Specification:
Mechanics Pistol Grip Pliers.
Long reach plier set with unique compound action joint for increased access in tight spaces .
Drop forged, full polished, Double color dipped grip
Straight nose or bent; 2-1/2" serration, wide grip range.
Dual position grip.

MY-PL1214

◆ MY-PL1214 LONG DIAGONAL CUTTING PLIER 8 INCH



Specification:
High leverage.
High-carbon C1080 steel for superior performance on the job and specially coated for ultimate rust prevention.
Increased reach into deep pocket areas.
Laser heat-treated cutting edges last longer."

MY-CU75

◆ MY-CU75 EXHAUST TAILPIPE CUTTER



Specification:
Exhaust and tailpipe chain type cutter.
This tool is used to cut pipes 0.75" to 3" (19 to 76mm) in diameter.
It has 15 blades that effectively cut pipe,so only a 0.25" rotation is needed for a complete cut.
The handles are plastisol-dipped for easy grip and comfort.
It will not cut double-wall pipes.
Not for use in stainless steel."

MY-CU76

◆ MY-CU76 PRO EXHAUST AND TAILPIPE CUTTER



Specification:
Use tool to cut pipes 3/4-Inch to 3-Inch in diameter.
Fifteen blades effectively cut pipe so only a quarter turn is needed for complete cut.
Tool works well in hard to reach areas.
Will not cut double wall pipes.
Not for use on stainless steel."

MY-SO39

◆ MY-SO39 EXHAUST PIPE EXPANDER SET 3PCS



Specification:
Sizes 1.1/8 to 3.1/2 inch.
Drop forged heat treated steel.
Works with all 1.1/8 - 3.1/2 inch thin walls.
Small expander 1.1/8 - 1.75 inch, medium expander 1.5 - 2.5 inch large expander 2-1/8 to 3-1/2 inch. "

MY-BJ24

◆ MY-BJ24 GEAR WRENCH UNIVERSAL BALL JOINT SEPARATOR



Specification:
Jaw opening:22mm.
For Separating the Ball Joint From the Spindle Support Arm on Domestic and Import Front Wheel Drive Vehicles
Adjustable for different size ball joints 1-1/8" & 2-1/8" (30 & 56mm) Maximum Opening Capacity
Applicable:Europe cars. "

MY-BJ02

◆ MY-BJ02 BALL JOINT EXTRACTOR SET 5PCS



Specification:
1pcs. Ball joint extractor (fork size 17.4mm)
1pcs. Ball joint extractor (fork size 23.8mm)
1pcs. Ball joint extractor (fork size 28.5mm)
Two exchangeable handles
Material forged carbon steel"

MY-BJ21

- ◆ MY-BJ21 AUTO BEARING RACE SEAL DRIVER DISC TOOL MASTER SET WHEEL AXLE BUSHING



Specification:Bearing Race and Seal Bush Driver Set Master Universal Kit for Automotive Wheel Bearings
Practical: The ABN Bearing Race and Seal Bush Driver Set with Carrying Case – Master / Universal Kit for Automotive Wheel Bearings allows for easy race seal installation without damaging the axle housing
Sizes: Includes 1 driver and 9 collar/discs: 1.565" , 1.750" , 1.965" , 2.325" , 2.470" , 2.555" , 2.830" , 2.995" , 3.180" ; Listed diameter is the diameter at the larger top side of the taper, not the end closest to the handle
Compatible: Collars fit standard race sizes used in most wheel bearing applications
Durable: Constructed from high-strength aluminum for extra strength and longevity; Won't mar the bearing
Easy Storage: Heavy-duty 10" x 5.8" x 4" (25.4cm x 14.7cm x 10.2cm) blow-molded plastic carrying case for easy transport, simple storage, and quick organization"

MY-BJ36

- ◆ MY-BJ36 BALL JOINT SPLITTER TIE ROD END PULLER 19MM



Specification:
 Professional tool for commercial or occasional use .
 Suitable for use on imports and front wheel drive vehicles including SUV's with rack and pinion steering.
 Centre tip on forcing screw swivels to help remove and prevent damage to the tie rod stud.
 Heat treated and drop forged for strength and durability when using this item.
 Opening size 19mm.
 Pull total travel 54mm."

MY-BJ25

- ◆ MY-BJ25 PULLY PULLER



Specification:
 This automotive pulley puller provides perfect pulls for one-and two-groove pulley on alternators and power steering pump in your vehicle.
 The pulley puller is constructed of drop-forged carbon steel for maximum durability and toughness to withstand heavy use.
 Adjustable jaw tension ensure a good grip as it pulls,making this a quality tool for any mechanic and car hobbyist repairing the inner workings of most vehicles.
 Heavy duty construction pulley puller.
 Adjustable jaw tension.
 Also removes some alternator bearings.
 Drop-forged,machined and heat-treated carbon steel construction.
 Jaw opening:1-3/8" .

MY-BJ35

- ◆ MY-BJ35 TIE ROD END REMOVER



Specification:
 Outer Tie Rod Remover
 Two adjustable jaws special designed for removing .
 Most models of outer the rod.
 Material:SCM420 Hardened 42. Packing:each /double blister
 6sets/24sets/29kgs/30kgs/2.3"

MY-BJ46

- ◆ MY-BJ46 BALL JOINT ANCHOR PIN PRESS SET



Specification:
 This tool kit is designed for use on all cars and light trucks that have press fit type ball joints without need to remove the control arm from the vehicle with 4wheels drive adaptors brack anchor pin removal & installation frame & forcing screw installation adaptor removal adaptor installation cups receiving tubes clamp max load: 4tons"

MY-WT05

- ◆ MY-WT05 WHEEL BEARING REMOVER KIT



Specifications:
 Bearing Size: 72 mm
 Pressure Plate With 8 Secondary Bores Size: 122*122*18mm
 Package Size: 31*23*9cm
 Tools Color: Black
 Case Color: Red
 Material: Carbon Steel
 Suitable for: For Audi A1 (from the year 2011), For Audi A2 (built after 2000), For Seat Ibiza (from 2002), For Skoda Fabia (manufactured since 2000), For VW Fox (starting from 2005) For VW Polo.

Package Included:
 1 x Pressure Plate With 8 Secondary Bores
 5 x Pressure Bolts
 1 x Threaded Spindle M 20 X 2.0, With Nut Hexagon Drive 22 MM
 1 x Pair Of Half-Shells For Disassembly (72 MM)
 1 x Disassembly Plate
 1 x Pair Of Half-Shells For Installation (72 MM)
 1 x Mounting Plate
 1 x Plastic Case"

MY-BJ63

◆MY-BJ63 QUICK CHANGE BALL JOINT REMOVER



Specification:
Innovative quick change and simple action for suitable work.
Enable operator for select correct law size with taking entire extractor to the vehicle.
Adjustable opening angel
Jaw opening: 20, 22, 24, 27, 30mm
Pivot rod length: 125mm"

MY-BJ64

◆MY-BJ64 BALL JOINT EXTRACTOR SET 3PCS



Specification:
A three pcs ball joint remover set for use in confined spaces.
Suitable for a number of makes of vehicle. Including: Audi, BMW, Ford, Chrysler, Opel, Saab, Volvo, VW, Nissan, Toyota.
Sizes included: 23mmX55mm, 28mmX55mm, 34mmX63mm.
Supplied in a bow mould case for storage."

MY-BJ202

◆MY-BJ202 FRONT END SERVICE TOOL SET 5PCS



Specification:
1pcs. Pitman arm/Tie rod end puller
1pcs. Ball joint separator
1pcs. Pitman arm puller
1pcs. Ball joint/Tie rod end remover
1pcs. Tie rod/Bearing race puller"

MY-PB05

◆MY-PB05 PRESS AND PULL SLEEVE KIT 27PCS



Specification:""5pcs. Pulling spindles (M10, M12, M14, M16, M18)
22pcs. Press sleeve:
34/44mm
36/46mm
38/48mm
40/50mm
42/52mm
44/54mm
46/56mm
48/58mm
50/60mm
52/62mm
54/64mm
56/66mm
58/68mm
60/70mm
62/72mm
64/74mm
66/76mm
68/78mm

MY-PB08

◆MY-PB08 UNIVERSAL INJECTOR SEALING SEAT CLEANING SET 22PCS



Specification:
1pcs. Slide hammer 4.8kg
1pcs. Universal joint M18x15
1pcs. Special hex bit insert 1/2"" dr. 10mm Ø7.5mm
1pcs. Special hex bit insert 1/2"" dr. 10mm Ø6.5mm
6pcs. Injector disassembly adapter M14x1.5 (BMW M47 211 CDI)
M16x1.0 (Toyota 2.2)
M17x1.0 (MB Bosch)
M20x1.0 (Denso)
M25x1.0 (Siemens)
M27x1.0 (Siemens)
1pcs. Plastic box""

MY-PB06

◆HYDRAULIC GEAR PULLER



Specification:
Effective bearing puller and gear puller. Extracts with minimal effort by use of the hydraulic puller. Six position multi-function puller with adjustable two or three leg function giving the mechanic an effective puller tool for various job types.

The blow-molded storage case is well designed for a long life in daily use and for easy transportation. Shankly' s hydraulic puller set includes, hydraulic pump, 3 puller legs, 6 nuts and washers, 6 link plates, leg puller yoke, nose adapter, Min/Max Reach 0 - 150mm, Min/Max Spread 100 - 240mm, screw rod: SAE 1045, bearing: SAE 5140.

Shankly' s heavy duty 3-jaw gear puller is remarkably versatile, perfect for automotive mechanical installation, extraction and even railway vehicle maintenance. Removes pulley, bearings, gears and other components."

MY-PB20

◆MY-PB20 BEARING SEPARATOR SET 9PCS



Specification:
1 x φ15-58mm Separator.
2 x 50mm Jaw.
1 x Thrust Screw.
2 x 45mm Extension Rod.
2 x 30mm Extension.
1 x Cross Beam.
Compact set containing bearing separator, yoke and extensions.
Chrome Vanadium components ensure long tool life.
Suitable for removing small gears, wheels and fitting from shafts.

MY-PB10

◆ MY-PB10 SEAL DRIVE SET, BUSHING REMOVAL TOOL 50 PCS



Specification:

18mm, 25/32"; 43mm, 1-11/16"; 19mm, 3/4"; 44mm, 1-23/32"; 20mm, 25/32"; 45mm, 1-25/32"; 21mm, 27/32; 46mm, 1-13/16"; 22mm, 7/8"; 47mm, 1-27/32"; 23mm, 29/32"; 48mm, 1-15/16"; 24mm, 15/16"; 49mm, 1-31/32"; 25mm, 1"; 50mm, 2"; 26mm, 1-1/16"; 51mm, 2-1/32"; 27mm, 1-1/16"; 52mm, 2-1/16"; 28mm, 1-3/32"; 53mm, 2-1/8"; 29mm, 1-5/32"; 54mm, 2-3/32"; 30mm, 1-3/16"; 55mm, 2-5/32"; 31mm, 1-7/32"; 56mm, 2-7/32"; 32mm, 1-1/4"; 57mm, 2-1/4"; 33mm, 1-9/32"; 58mm, 2-9/32"; 34mm, 1-11/32"; 59mm, 2-11/32"; 35mm, 1-3/8"; 60mm, 2-3/8"; 36mm, 1-13/32"; 61mm, 2-13/32"; 37mm, 1-15/32"; 62mm, 2-7/16"; 38mm, 1-1/2"; 63mm, 2-1/2"; 39mm, 1-17/32"; 64mm, 2-17/32"; 40mm, 1-19/32"; 65mm, 2-9/16"; 41mm, 1-5/8"; 74mm, 2-29/32"; 42mm, 1-21/32".

All pieces come in a heavy duty blow molded case with compartments for every piece."

MY-PB27

◆ MY-PB27 TIMING GEAR PULLER 5"



Specification:

Size: 5" .
Removes timing gears, fan pulleys, balancers and other automotive components with tapped holes.
Drop forged, plated steel yoke resists corrosion.
Heat treated center bolt."

MY-PB020

◆ MY-PB020 BEARING SPLITTER GEAR PULLER FLY WHEEL SEPARATOR SET TOOL KIT 14PCS



Specification:

This bearing puller set can remove gears, pulleys and steering wheels efficiently. It is suitable for splitting bearings on cars and commercial vehicles.
All tools are well stored in a sturdy case for better storage.
Ideal for removing gears, pulleys and steering wheels
This bearing puller set is suitable for splitting bearings on cars and commercial vehicles.
The heavy duty steel and oxide finish ensure a long-term service life.
Crafted by drop forged, heavy duty steel, this bearing puller set is endowed with maximum durability for years of use.
Delivery includes: 14 pcs
2 x Bearing splitters (2" and 3" jaws) (1.2"-2" & 2"-3")
1 x H-type beam
1 x Lead screw
2 x 6" Yoke adaptor
2 x 5" Extension screw with male and female threads
2 x 4" Extension screw with male and female threads
2 x 5" Extension screw with male threads
2 x 4" Extension screw with male threads"

MY-PB29

◆ MY-PB29 2-JAW LIGHT DUTY GEAR PULLER 3.5"



Specification:

For light-duty pull jobs including battery cables, wind-shield wiper arms, banjo bolts, pulleys, seals, etc.
shaped jaws, pivoting center screw, 4" spread, 3" reach.
Zinc plated to prevent corrosion .
Made to be the most reliable tools in the market today.
Tool solutions for most all situations.
Built to exceed tool standard."

MY-PB38

◆ MY-PB38 5" 2-JAW GEAR PULLER



Specification:

For light-duty pull jobs including battery cables, wind-shield wiper arms, banjo bolts, pulleys, seals, etc.
shaped jaws, pivoting center screw, 6" spread, 4" reach.
Zinc plated to prevent corrosion .

MY-PB75

◆ 9PC INTERNAL BEARING PULLER SET



Specification:

8 - 10MM (51/6" - 13/32")
10 - 12MM (13/32" - 15/32")
12 - 14MM (15/32" - 9/19")
15 - 17MM (9/32" - 11/16")
17 - 20MM (11/16" - 25/32")
20 - 24MM (25/32" - 15/16")
25 - 29MM (1" - 1-1/8")
30 - 32MM (1-3/16" - 1-1/4")

HAMMER WG. 100MM / L - 2. 15LB (940G)
3 POUND SLIDE HAMMER WITH T - HANDLE

DROP FORGED HEAT TREATED STEEL ATTACHMENTS

HEAT TREATED PRECISION MACHINED STEEL BOLTS

REMOVES GEARS, PULLEYS, & STEERING WHEELS

SEPARATES BALL BEARINGS

SLIDE HAMMER SHAFT 390MM L

Listing inCluding :

1 x Inner Bearing Puller Set Remover Slide Hammer Internal Kit 8-32mm 9pc Blind Hole"

MY-PB226

◆MY-PB226 CAMSHAFT SPROCKET PULLEY PULLER



Specification:
1 x 23mm wide spokes for odd number of spokes.
1 x 17mm narrow for spokes.
2 x universal tool for even number of spokes.
1 x Hex head 17mm with ball end for reducing damage to sprocket.
Enables the camshaft sprocket removal on a wide range of vehicles. Supplied with two length of arms for universal application.

Instructions:

- Select the arms required and hold the sprocket in place.
- Undo the retaining bolt or nut and remove.
- Slacken off the three bolts that hold the adjustable legs, (make sure the centre bolts is would back far enough not to interfere with the camshaft centre).
- Fit the slots in the legs around the centre web holes in the sprocket.
- Tighten the leg holding bolts in to position.
- Now tighten the centre bolt in the puller up against camshaft drawing off the camshaft sprocket.

MY-PB234

◆MY-PB234 SMALL PITMAN ARM PULLER



Specification:
Heavy duty forged alloy steel yoke.
Heated treated center screw.
Remove the rod ends and pitman assemblies from many light trucks.
Opening size :27mm.
Pull travel: 45mm

MY-PB233

◆MY-PB233 PITMAN ARM PULLER 33MM



Specification:
1-5/16" (33mm) pitman arm puller is designed to handle the toughest pitman arm pulling jobs on passenger cars and light trucks.
The yoke features drop forged construction and is heat treated for strength and durability.
The jaws are shaped to ensure a positive grip, which leaves your hands free for the pulling job.
This tool has a 1-5/16" (33mm) Yoke opening and is designed to remove the Pitman arms from domestic cars and light trucks.
The 3/8" drive square port in the center screw allows for the tool to be used with a 3/8" drive ratchet.

MY-PB240

◆MY-PB240 REAR SUSPENSION TOOL



Specification:
Rear suspension tool for trailing arm bushes. Ford Focus Mk 1 & II (98-07)(07<-) | Kuga 2008< | C-Max MPV 2007 | Mazda 3 (Chassis BK) 2003<09 Saloon and Hatchback, 5 (Chassis CR, CW) MPV | 2005 Volvo V50 Estate 2004<2012, S40 Mk II Saloon 2003<2012.
Always lubricate the bar thoroughly before and after use.
Bar is considered consumable and available as a spare part (Part No 2169).
Adequate and appropriate lubricants to be used on threaded force screws and thrust bearing (Laser Tools Recommends Molybdenum Disulphide Grease (black drive shaft grease)."

MY-PB28

◆17PCS MASTER FRONT WHEEL DRIVE BEARING SERVICE KIT



Specification:
Comprehensive set for the removal and installation of front hub bearings without the need to dismantle the steering assembly.
May be used with an Impact Wrench Heavy Duty Steel Drifts
Hub Screws - M12 x 1.5 and M14 x 1.5mm
Drift sizes - 55.5. 59. 62. 65. 66. 71.5. 73. 78. 84. 86. 91mm
Suitable for most front wheel drive cars and vans"

MY-PB921

◆MY-PB921 CHAMSHAFT HOLDING TOOL



Specification:
Suitable for positioning of camshafts when timing engine or rebuilding cylinder head.
Adjustable peg to allow for varying pulley and belt thickness."

MY-SC211

◆MY-SC211 VALVE SPRING COMPRESSOR



Specification:
Suitable for the replacement of valve springs and valve stem oil seals without the need to remove the cylinder head.
Use in conjunction with VS 1601 compressed air adaptor.
Adjustable handle, claws and hooks allow use on most OHV engines."

MY-SC02

◆ MY-SC02 UNIVERSAL COIL SPRING COMPRESSOR



Specification:

STRONG AND SECURE HOOKS REDUCE SLIPPAGE: Avoid strut compressors with flimsy hooks creating slippage and other safety problems. Shankly's coil spring compressor hooks grip springs tightly by turning easy to use hex nuts.

UNIVERSAL COMPRESSOR TOOL: Impressive jaw capacity (23 mm - 280 mm) make Shankly's coil spring compressor tool is ideal for a range of vehicles, assisting the mechanic with years of compression jobs. MAKES SPRING COMPRESSION SAFER: Compressing struts and springs can be dangerous. Shankly's strut spring compressors feature lower security jaws and adjustable safety bars reduce work site perils.

SAFETY FIRST: Spring strut compressor work can be perilous if not performed with care. Shankly's heavy duty spring compression tool includes lower security jaws and adjustable safety bars to better protect to worker. Shankly's strut spring compressor tool is usable with 19 mm hex socket or wrench.

DURABLE AND TOUGH: Shankly's heavy duty spring compressor for struts features rugged and durable frames, reducing bending and warping even under high tension. Shankly strut spring compressors bear an impressive 1200 kg maximum capacity per pair, making these coil spring compressors usable for most any vehicle make including large cars and trucks. WIDE JAW CAPACITY: Avoid a coil compression tool with unsecured and flimsy hooks which can cause slippage and safety concerns, Shankly's strut coil spring compressor easy turning hex nuts grip springs securely and reduce safety concerns. This strut compressor features a wide jaw capacity (23mm - 280mm)."

MY-SC10

◆ MY-SC10 INTERCHANGEABLE FORK SPRING COMPRESSOR



Specification:

Interchangeable jaws are easily changed to correct size for the application
Compressor Body Shaft
80-115 mm Yokes
110-150mm Yokes
140-195mm Yokes
conical spring adapter
Blow molded case
Maximum jaw opening is 300mm"

MY-SC210

◆ MY-SC210 TOOLSEMPIRE OVERHEAD VALVE SPRING COMPRESSOR SEAL ON ENGINE KEEPER REMOVE INSTALL TOOL



Specification:

This overhead valve spring compressor features a reversible jaw / adaptor and automatic cam-action locking to a re-determined setting. For use on a wide range of OHV, OHC and CHV engines, very easy to use as a good helper. Cam action level design for secure valve spring locking into the tool. Allow valve springs and valve stem oil seals to be replaced with the cylinder head. Tool spring depth reach grips to retainer are adjustable to fit most large and small spring applications. Ideal for removing valve springs, spring retainers by compressing the valve spring retainer and exposing the valve keeper, remove keepers, uncompress the tool then remove spring."

MY-SC13

◆ MY-SC13 MACPHERSON SPRING COMPRESSOR (300MM)



Specification:

A special tool for use on all vehicles. Equipped with macpherson struts to rapidly compress the oil spring to enable replacement of shock absorbers, spring sets, repair bent sturts and damaged spindles. Drop forged jaws with safety pins to provide a safety performance."

MY-SC26

◆ MY-SC26 PERFORMANCE TOOL OVERHEAD VALVE SPRING COMPRESSOR



Specification:

Conveniently removes valve springs on most cars and light trucks without removing cylinder head
Offset jaws easily grip and compress valve springs
Requires Flexible Air Valve Holder (PT W84003) and Air Hold Fittings (PT W84005) to keep valves from dropping into cylinders when keepers are removed"

MY-SC14

◆ MY-SC14 SPRING COMPRESSOR FOR MERCEDES



Specification:

Drop forged yokes heat treated Telescopic construction with 3 point safety interlocks and automatic freesheel end or stoke Max. compression range: 325mm Min. compression range: 120mm"

MY-UCR223

◆ MY-UCR223 FLYWHEEL TURNER



Specification:

Flywheel Turner
Use this special wrench to turn the flywheel and rotate the engine.
Folds for easy storage.
Also holds the flywheel or flex plate when torquing the flywheel or harmonic balancer bolts."

MY-TT16

◆ MY-TT16 ENGINE TIMING TOOLS SET-AUDI-VW-SKODA



Specification:

Applicable: Audi A4, A6, A8, A11 (97-08) , abd VW since 98.
Engine codes: AFB, AKE, AKN, AYM, BAU, BCZ, BDG, BDH, BFC etc....
A comprehensive engine timing tool set for the VAG group both petrol and diesel engines.
Applicable: Audi A4, A6, A8, A11 (97-08) , abd VW since 98.
Engine codes: AFB, AKE, AKN, AYM, BAU, BCZ, BDG, BDH, BFC etc....
Includes the tools for Vehicles with modified engine mounts
Locking pin(s) for 1.8, 1.8T, 2.0, 16v
Timing tool for camshaft and crankshaft when changing the timing chain on the 1.2, 12v three cylinder engine.
For injection and diesel engines for locking the clamping element in replacing the V-ribbed belt.
Camshaft adjustment tool.
Chain tensioner tool.
Timing tool for cam and crankshafts 2.5l tdi v6 and 3.3l v8 tdi (Audi A8)
Locking tool to the oval crankshaft wheel 2.0l tdi pump nozzle.
Large range of fixing pins.
Fixing mandrel tool V6/ V8 petrol, diesel
Camshaft adjustment tool for 1.9l tdi and sdi without disassembling the valve cover.
Camshaft locking tools.
Tool for diesel fuel injectors SW22
A range of mandrels for pump locking

MY-SC212

◆ MY-SC212 VALVE SPRING COMPRESSOR FOR UNIVERSAL USE ON SHOC AND DOHC ENGINES



Specification:

2 x Support bar .
1 x Spark plug air-line adaptor .
2 x adjustable upright.
1 x Compressor force screw assembly .
1 x Valve adaptor.
1 x Extension rods.
Design to allow the removal of valve stem oil seals with the cylinder head in place.
Fast set up time due to the twin ratio pivot system.
Single handed operation."

MY-TT46

◆ LOCKING CHAIN CAMSHAFT ADJUSTMENT INJECTION PUMPS TOOL SET



Specification:

Opel Z 19 DT / Z 19 DTH engine (OHC and DOHC) e.g. in Vectra C and Signum '04
Opel Z13 DT engines e.g. in Corsa and Combo '04
Opel with Z 22 SE engine in Astra G, Vectra C, Zafira, Signum and Speedster Vx220 since '00 - '04
Opel with 1.0l - 12V, 1.2l and 1.4l 16V petrol engines (X10XE, Z10XE, Z10XEP, X12XE, Z12XE, Z14XEP) e.g. Corsa, Agila, Astra and Meriva
Opel 2.0l and 2.2l Ecotec diesel-engines (X20DTL, X20DTH, X22DTH) e.g. Astra, Astra, Caravan, Zafira, Vectra, Omega, Sintra and Frontera
Engines may be identical in construction to Renault and Saab"

MY-UCR62

◆ MY-UCR62 EXHAUST TOOL SET 4PCS



Specification:

1 x nut splitter.
2 x pipe expanders .
1 x pipe cutter.
For servicing, installing and repairing exhaust pipes, including cutting pipe up to 3-1/2". diameter, flaring and dent removal.
Lifetime warranty on tools, replacement parts available.
Step by step usage instructions and photos showing the tool in use instruction sheets are laminated to resist staining and are permanently fastened to the case .
Meets or exceeds ANSI standards
Includes heavy duty storage case.

MY-UCR224

◆ MY-UCR224 NUT SPLITTER SET 4PCS



Specification:

15/16"-1/2"(9-12mm)
1/2"-5/8"(12-16mm)
5/8"-7/8"(16-22mm)
7/2"-11/18"(22-27mm)
For the safe removal of corroded or damaged nuts without damaging bolt threads.
Drop forged steel body hardened and tempered with chrome plated.
Threaded splitting pin manufactured from chrome vanadium steel with black phosphate finish.
Packed in blow molded case."

MY-TT11

◆ MY-TT11 ENGINE TIMING TOOL SET-RENAULT



Engine:
1.4,1.6,1.8,2.0 16V,
camshaft V-belt pulley locking tool
Suitable for:Dacia:
Logan 1.6Renault:
Megane, Clio, Clio Sport, Scenic,
Laguna (98-08);
Espace, Clio Sport (98-04); Megane II.,
Scenic II.,
Gran Scenic II., Laguna II. (02-09), Megane II.
(02-05), Laguna II. (01-05)
Engine code:
K4J 712/713/730/732/750,
K4M 700/701/720/724/748/760/761/764,
F4P 720/722/760/770/771,
F4R700/701/730/740/741/744/770/771/776/
780/784/786/787

MY-TT04

◆ ENGINE TIMING TOOL-FORD-MAZDA



Specification:
Includes adjusting gauge for camshaft,
crankshaft, pumpshaft
Complete Classification chart included
For e.g:
1.4 ltr. + 1.6 ltr 16v+1.7 ltr+ 1.8 ltr. 16V(also
Zetec)
-1.4 ltr. -1.6 ltr.-1.8 ltr. and 1.9 ltr. D/TD/TDCI"

MY-TT24

◆ MY-TT24 CAMSHAFT INSTALLATION AND TIMING TOOL SET - VOLVO



Material: 45# Steel
Engine:B4164S, Engine:B4164S2,
Engine:B4184S, Engine:B4184S10,
Engine:B4184S2, Engine:B4184S3,
Engine:B4184S9, Engine:B4184SJ,
Engine:B4194T, Engine:B4194T2,
Engine:B4204S, Engine:B4204S2,
Engine:B4204T, Engine:B4204T2,
Engine:B4204T2 CVVT, Engine:B4204T3,
Engine:B4204T3 (USA)(CDN),
Engine:B4204T4, Engine:B4204T5,
Engine:B5202FS, Engine:B5204FS,
Engine:B5204FT, Engine:B5204T2,
Engine:B5204T3, Engine:B5204T4,
Engine:B5204T5, Engine:B5234FS,
Engine:B5234FT, Engine:B5234T2,
Engine:B5234T3, Engine:B5234T4,
Engine:B5234T5, Engine:B5234T6,
Engine:B5234T7, Engine:B5234T8,
Engine:B5234T9, Engine:B5244S,
Engine:B5244S2, Engine:B5244S4,
Engine:B5244S5, Engine:B5244S6,
Engine:B5244S7, Engine:B5244SG,
Engine:B5244SG2, Engine:B5244T,
Engine:B5244T2, Engine:B5244T3,
Engine:B5244T4, Engine:B5244T5,
Engine:B5244T7, Engine:B5252FS,
Engine:B5254FS LH 3.2 , Engine:B5254FS M
4.3, Engine:B5254F
Applicable: VOLVO Models 850, 960, S40, S70
And S90
Popular Applications Include 700, 800, 850,
900, 960, C70 Coupe And Conv S40, S60, S70,
S80, S90, V70-2000, V70XC, XC70, V90, XC90
Models: S80 (07-), V70 (08-), S80 (-06), XC90,
V70 (00-08), V70 XC (01-) / XC70 (-07), S60,
C30, C70 (06-), S40 (04-), V50, S40 (-04), V40,
850, C70 Coupe (-02), C70 Conv (-05), S70,
V70 (-00), V70 XC (-00), 960, S90, V90
Engine: B41XX, B42XX, B52XX, B62XX, B63XX,
GB5252S
Data On The Press Tools (Volvo Ref 999
5454)(Threads: 14mmx1.5)"

MY-TT43

◆ LOCKING TOOL SET OPEL 1.3 CDTI



Specification:
Vauxhall / Opel 1.3 CDTI common
railVauxhall/ Opel Corsa, Combo Z13DT
engine.
To prevent the engine shafts (e.g. camshafts,
crankshaft) from turning or to keep them in a
specific position and to adjust the timing
belt tensioner when changing a timing belt
or during other engine repairs."

MY-TT57

◆ ENGINE TIMING TOOL SET FOR AUXHALL/OPEL 1.0/1.2/1.4



Specification:
Checking and Adjustment of Timing.
Installing and Removal of
Camshaft/Variable Camshaft Timing Unit."

MY-TT93

◆ ENGING TIMING TOOL VW/ SKODA/SEAT



Specification:
ALL PACKED IN BMC.
- To test and adjust the engine timing.
- For 1.0L 3 cyl. Gasoline engines VW up,
SEAT Mii frome Bj.
2011 SKODA Citigo."

MY-TT103

◆ MY-TT103 ENGINE TIMING TOOL SET-RENAULT



Engine:
Double camshaft 1.2, 1.4,1.6,1.8,2.0 16V, 2.2D, TD, 2.2Td, 2.2TD, 2.5D, 2.5D, TD with timing belt
Suitable for:
Renault Clio, Clio Sport, Clio Williams, Twingo, Kangoo, Laguna, Safrane, Espace, Scenic, Trafic, Master, Express
Brand: Lincos
Category: Dacia
Product-SKU: FB2715
Weight:

MY-TT05

◆MY-TT05 PETROL ENGINE SETTING/LOCKING KIT - BMW



Suitable for timing 1.8/2.0 Valvetronic chain drive petrol engines.
Includes all the tools to align the twin vanos units.
Supplied in carry-case.
Applications:
BMW; 118/120 E81 E82 E87 (04-09), 318/320 E90 E91 E93 (05-09), Z4 E85 E86 (04-09), X3 E83 (05-09), 316/Compact E46 (01-05), 318/Compact E46 (01-07)"

MY-TT03

◆ CAMSHAFT ALIGNMENTTIMING TOOL SET BMW



"Feature:
Master tool set contains a comprehensive set of tools to perform camshaft + VANOS timing on M52TU, M54, M56 Engines. The tools are also applicable for camshaft timing on non-VANOS engines (M42, M44, M50, M52, MS50US and S52US).
The kit includes the following:
KTC-B1121 BMW Double VANOS Camshaft Alignment Tool:
This five-piece kit contains all the tools necessary to assemble and time the VANOS cam-timing units on BMW M52TU, M54 and M56 6-cylinder engines utilized from 1998 onwards.
KTC-A1137 BMW VANOS Sprocket Wrench M50 M52 S50 S52:
Special wrench designed specifically to turn camshaft sprockets when removing or installing the VANOS variable valve timing unit.
KTC-A1033 BMW 4 & 6 Cylinder Camshaft Alignment / Timing Tools:
This tool kit contains all the necessary, engine-specific tools to time the camshafts in BMW M42, M44, M50, M52, M52TU, M54, M56, MS50US and S52US engines. Includes: Camshaft alignment jig to fix the camshafts in the proper orientation during assembly and Top dead center pin to align the flywheel at the TDC position

MY-TT06

◆PETROL ENGINE SETTING/LOCKING SET-BMW



Kit comprises camshaft locking tools and flywheel locking pin.

MY-TT02

◆ MY-TT02 BMW CAMSHAFT ALIGNMENT AND ENGINE TIMING TOOL N51/N52/N53/N54



BMW N51/N52/N53/N54 Camshaft Alignment and Timing Tool
Package Includes:
VANOS Alignment Plates
TDC Locking Pin
CAM Alignment jig
2 Setting Gauges
1 blow mold case
Application:
For 2006 and newer vehicles Series 1, 3 and 5 Models, (N52) 3.0L (Non-Turbo), (N54) 3.0L Twin Turbo engines.
E60 (523i, 523Li, 525i, 525Li, 525xi, 528i, 528xi, 530i, 530Li, 530xi, 535i, 535xi), E61 (523i, 525i, 525xi, 530i, 530xi, 535xi, E63 (630i), E64 (630i), E65 (730i), E66 (730Li), E70 (X5 3.0Si), E81 (130i), E82 (135is), E83 (X3 2.5i, 2.5Si, 3.0i, 3.0Si), E85 (Z4 2.5i, 2.5Si, 3.0i, 3.0Si), E86 (Z4 3.0Si) E87 (130i), E90 (323i, 325i, 325xi, 328i, 328xi, 330i, 330xi, 335i, 335xi), E91 (323i, 325i, 325xi, 328i, 328xi, 330i, 330xi, 335i, 335xi), E92 (323i, 325i, 325xi, 328i, 328xi, 330i, 330xi, 335i), E93 (325i, 328i, 330i, 335i)

MY-TT12

◆ AUXILIARY STRETCH BELT REMOVAL TOOL



Application:
BMW118 120 X3 X5 /Chrysler Grand Voyager, Voyager/Citroen C2 C3 C4, Jumper, Relay/Fiat Albea Doblo Marea Multipla Ducato Fiorino Qubo Linea Siena Stilo Strada/Lancia Lybra/Ford C-Max Focus Mondeo Tourneo Transit Courier Fiesta Fusion/Iveco Daliy/Peugeot 206 207 307 Boxer/Volvo C30 C40 V50"