Product image	Description	FOB	Qty	Unit price	Leadtime
CF-20L	20L mini fridge with DC/AC power; Size: W234MMXD220MMXH380MM for inside, & 20L mini fridge with DC/AC power; Size: W234MMXD220MMXH380MM for inside, & W306MMXD397MMDH452MM for outside; Packing: 1pc in a color box, and packing size W410MMXD325MMXH470MM; Quantity for 1x20' container: 500pcsW306MMXD397MMDH452MM for outside; Packing: 1pc in a color box, and packing size W410MMXD325MMXH470MM; Quantity for 1x20' container: 500pcs	Shanghai	500	US\$42.80	35days
USB cup	Capacity: 0.5L Voltage: DC12V or USB powered Cooling capacity: 18~20°C below ambient temperature. Heating capacity: 60±10°C by set point thermostat. Hot/Cold,On/Off switch. Power consumption 36~68W. 100%CFC and HFC-free. Optionai DC 12V and USB power supply. Ideal for your car,boat,office home.usb poweres with Aluminum cup for cooling Beverage Production measure: 11×15×14.5cm Gift box measure: 70.5×48×38cm/16PCS Weight: N.W: 0.8kg G.W:1.0kg Loading quantity: 20'GP:3968PCS, 40'GP:7088PCS & 40'HQ:8080PCS.	NINGBO	1000	US\$11.20	35days
CF-U0701	Cools a can coke from 5V USB power, 8W Stylized as a mimi fridge Holds one can. Internal LED light USB powered No batteries required Temperature of cooling pad decreases to 8.5 degrees after 5 minute Temperature of heating pad decreases to 45 degrees after 5 minute Dimension: (H)11.5×9.5×9.5cm Carton: 60pcs/ctn:47.5×34.5×38cm Weight:300g quantity: 20' GP:30600PCS, 40' GP:61920PCS, & 40' HQ:67680PCS	NINGBO	1000	US\$8.15	35days

CF-0804B	Volume: 4L Voltage: DC12V & AC100-240V Power consumption: DC: cold mode/40W, Hot model/52W AC: cold mode/56W, Hot model/52W Cooling capacity: 15℃-18℃ below ambient temperature Heating capacity: 60℃ Insulation: adopts thermoelectric technology(peltier system)solid polythane foam Production unite: 31×31×27.8cm Gif measure: 32×29×30.7cm Carton: 2PCS/CTN:59×33×32cm Loading quantity: 20' GP:900PCS, 40' GP:1964PCS, & 40' HQ:2240PCS.	NINGBO	1000	US\$22.50	35days
CF-0804A	Volume: 4L Voltage: DC12V & AC100-240V Power consumption: DC: cold mode/40W, Hot model/52W AC: cold mode/56W, Hot model/52W Cooling capacity: 18℃-20℃ below ambient temperature Heating capacity: 60±10℃ Insulation: adopts thermoelectric technology(peltier system)solid polythane foam Production measure: 26.5×25×31cm Gif box measure: 31×28.5×35.5cm 2PCS/Carton: 58×32×37cm; Loading quantity: 20' GP:840PCS, 40' GP:1728PCS, & 40' HQ:2016PCS.	NINGBO	1000	US\$19.05	35days
CF-0205B	Volume: 5 litres Voltage: DC12V & AC100-240V Power consumption: DC:Cold mode:40W±20%;	NINGBO	1000	US\$28.50	35days

CF-0506A	Volume: 6litres Voltage: DC12V & AC100-240V Power consumption: DC: Cold mode/40W±20%, Hot mode/32W±20%; AC: Cold mode/56W±20%, Hot mode/52W±20%; Cooling capacity: 20°C-25°C (68-77°F) below ambient temperature Heating capacity: 65°C (149°F) Insulation: adopts thermoelectric technology(peltier system) solid polyurethane foam Packaging unit: Each in a colour gift box(35.5×19×30.5cm) 5PCS/carton 96×36.5×32.5CM Loading quantity: 20'GP:1170PCS; 40'GP: 2380PCS; & 40'HQ:2720PCS.	NINGBO	1000	US\$21.50	35days
CF-0307A	Volume: 7 litres Voltage: DC12V & AC100-240V Power consumption:	NINGBO	500	US\$27.40	35days
CF-0307A	Volume: 7 litres Voltage: DC12V & AC100-240V Power consumption: DC: Cold mode/40W±20%, Hot mode/32W±20%; AC: Cold mode/56W±20%, Hot mode/52W±20%; Cooling capacity: 20℃-25℃ below ambient temperature; Heating capacity: +55℃ Insulation: adopts thermoelectric technology(peltier system) solid polyurethane foam Packaging unit: Each in a colour gift box(33×32.5×35cm) 2PCS/carton 65.6×35×38cm Loading quantity: 20'GP:656PCS; 40'GP:1354PCS; & 40'HQ:1520PCS	NINGBO	500	US\$27.40	35days

	Volume: 4 Litres Voltage: DC12V & AC100-240V Power consumption: DC: Cold mode/40W±20%, Hot mode/32W±20%; AC: Cold mode/56W±20%, Hot mode/52W±20%; Cooling capacity: 15-20°C below ambient temperature; Heating capacity: 55°C Insulation: adopts thermoelectric technology(peltier system) solid polyurethane foam Packaging unit: Each in a colour gift box(26.5×19.5×25.5cm) 8PCS/carton 54.5×41×54.5cm.	NINGBO	1000	US\$18.30	35days
CF-0704A	or od, out on one thorsoon.				
CF-0704A	Volume: 4 Litres Voltage: DC12V & AC100-240V Power consumption: DC: Cold mode/40W±20%, Hot mode/32W±20%; AC: Cold mode/56W±20%, Hot mode/52W±20%; Cooling capacity: 15-20°C below ambient temperature; Heating capacity: 55°C Insulation: adopts thermoelectric technology(peltier system) solid polyurethane foam. Colour gift box measure: 26.5×19.5×25.5cm; 8PCS/carton 54.5×41×54.5cm.	NINGBO	1000	US\$18.30	35days
CF-0204A	Volume: 4.5 litres Voltage: DC12V & AC100-240V; Power consumption: DC: Cold mode/40W±20%, Hot mode/32W±20%; AC: Cold mode/56W±20%, Hot mode/52W±20%; Cooling capacity: 15-20°C below ambient temperature; Heating capacity: 55°C Insulation: adopts thermoelectric technology(peltier system) solid polyurethane foam Packaging unit: Each in a colour gift box(26×19.1×28cm) 5PCS/carton 100×27.5×30cm; Loading quantity: 20'GP:1600PCS; 40'GP:3360PCS; 40'HQ:3840PCS.	NINGBO	1000	US\$18.30	35days

CF-0204B	Volume: 4 litres Voltage: DC12V & AC100-240V; Power consumption: DC: Cold mode/40W±20%, Hot mode/32W±20%; AC: Cold mode/56W±20%, Hot mode/52W±20%; Cooling capacity: 15-20°C below ambient temperature; Heating capacity: 55°C Insulation: adopts thermoelectric technology(peltier system) solid polyurethane foam Packaging unit: Each in a colour gift box(26×19.1×28cm) 5PCS/carton 100×27.5×30cm. Loading quantity: 20'GP:1600PCS; 40'GP:3360PCS; 40'HQ:3840PCS	NINGBO	1000	US\$18.30	35days
CF-0715A	Volume: 15 Litres Voltage: DC12V & AC100V-240V; Power consumption: DC: cold mode/60W±20%, Hot mode: 52W±20%; AC: Cold mode:56W±20%, Hot mode: 52W±20%; Cooling capacity: 15℃-20℃ below ambient temperature Heating capacity: 55℃ Insulation: adopts thermoelectric technology(peltier system)solid polythane foam Feature: With LED display,internal temperature is read at a giance. Gift box measure: 32.3×31.5×42.3cm; 2PCS/Carton:65×34×44.5cm. Loading quantity: 20'GP:570PCS; 40'GP:1230PCS; 40'HQ:1470PCS	NINGBO	500	US\$41.90	35days
CF-0715B	Volume: 15 Litres Voltage: DC12V & AC100V-240V; Power consumption: DC: cold mode/60W±20%, Hot mode: 52W±20%; AC: Cold mode:56W±20%, Hot mode: 52W±20%; Cooling capacity: 15°C-20°C below ambient temperature Heating capacity: 55°C Insulation: adopts thermoelectric technology(peltier system)solid polythane foam Feature: With LED display,internal temperature is read at a giance. Gift box measure: 32.3×31.5×42.3cm. Loading quantity: 20'GP:570PCS; 40'GP:1230PCS; 40'HQ:1470PCS	NINGBO	500	US\$36.50	35days

CF-0715C	Volume: 15 Litres Voltage: DC12V & AC100V-240V; Power consumption: DC: cold mode/60W±20%, Hot mode: 52W±20%; AC: Cold mode:56W±20%, Hot mode: 52W±20%; Cooling capacity: 15°C-20°C below ambient temperature Heating capacity: 55°C Insulation: adopts thermoelectric technology(peltier system)solid polythane foam Feature: With LED display,internal temperature is read at a giance. Gift box measure: 32.3×31.5×42.3cm. 2PCS/Carton:65×34×44.5cm. Loading quantity: 20'GP:570PCS; 40'GP:1230PCS; 40'HQ:1470PCS.	NINGBO	500	US\$40.60	35days
CF-0322A	Volume: 22litres Voltage: DC12V & AC100-240V; Power consumption: DC: Cold mode/40w±20%, Hot mode:32W±20%; AC: Cold mode:56w±20%, Hot mode:52W±20%; Cooling capacity: 15°C-20°C below ambient temperature Heating capacity: +55°C Insulation: adopts thermoelectric technology(peltier system) solid polyurethane foam LEDtemperature display . with extension puller and wheels for easy moving Packaging unit: Each in a colour gift box(44.5×34.5×45cm) Loading quantity: 20'GP:400PCS; 40'GP:850PCS; 40'HQ: 850PCS	NINGBO	400	US\$45.70	35days
CF-0324A	Volume: 24 litres Voltage: DC12V only Power consumption: DC cold mode:40W±20%; Hot mode: 32W±20%; Cooling capacity: 15℃-20℃ below ambient temperature Heating capacity: 55℃ Insulation: adopts thermoelectric technology(peltier system)solid polythane foam Gift box measurer: 42×32.5×46.5cm. 2pcs/carton:63.5×43.5×47cm. Loading quantity: 20'GP:448PCS; 40'GP:898PCS	NINGBO	400	US\$28.00	35days

CF-0324A -N	Volume: 24 litres DC12V & AC100-240V; Power consumption: DC: Cold mode/40W±20%, Hot mode/32W±20%; AC:Cold mode:56W±20%, Hot mode: 52W±20%; Cooling capacity: 15°C-20°C below ambient temperature Heating capacity: 55°C Insulation: adopts thermoelectric technology (peltier system) solid polythane foam. Features: 1.this model can be used as a attemperator. 2.With a small tap.water come out easily. 3.Add without electric lid.lt change to cooler box Color box size: 39.5×28.5×44.5cm 2PCS/Carton:57.5×40.5×46cm. Loading quantity: 20'GP:556PCS; 40'GP:1156PCS. Volume: 25litres; Voltage: DC12V & AC100-240V;	NINGBO	500	US\$27.40	35days
CF-0525A	Power consumption: DC: Cold mode/40W±20%, Hot mode/32W±20%; AC:Cold mode:56W±20%, Hot mode: 52W±20%; Cooling capacity: 18°C-23°C below ambient temperature Heating capacity: 55°C Insulation: adopts thermoelectric technology (peltier system) solid polythane foam. Features: It's big size and can be placed at where you need it Such as car,boat. Pincnic sife.Home etc.With puller and two wheels for easy. Size of the product:50.3×27×37cm, 1pc in colour gift box, 2pcs/carton (carton size:67×57×46.5cm). Loading quantity: 20'GP:340pcs; 40'GP:706pcs	NINGBO	300	US\$36.40	35days
CF-0533A	Volume: 33litres Voltage: DC12V & AC100-240V; Power consumption: DC: Cold mode/40W±20%, Hot mode/32W±20%; AC:Cold mode:56W±20%, Hot mode: 52W±20%; Cooling capacity: 15°C-20°C below ambient temperature Heating capacity: 55°C Insulation: adopts thermoelectric technology (peltier system) solid polythane foam Features: 1. this model fixed with 2 cooling devices(peltier systems) 2. This model can be fix with double peltier cooling system so the cooling capacity is improve greatly. Each in color box(60×42.5×51cm). Loading q'ty:20'GP/196pcs,40'GP/380pcs, 40'HQ/473pcs.	NINGBO	350	US\$53.10	35days

Remarks:	*Price Valid for 30days. *Prices are based upon the qty of 20'ft. *Prices are based upon normal plugs(for car or home),if you *Logo printing cost:it depends on the colors,size,the way to petc. quantity is less than 1000pcs, you have to pay the extra addi *Color options: Any color is available if the qty reaches 500pc	rint,such as	s silk-scre	een,water-trans *Color box o the color box	fering printing : If your factory
Payment Terms:	T/T 30%deposit,70%before shippment				
CF-0602A	Volume: Bottle wine with diameter up to 90mm Voltage: DC 12V only; AC 100V-240V Power consumption: DC: Cold mode/40W±20%, Hot mode:32W±20%; AC: Cold mode/56W±20%, Hot mode:52W±20%; Cooling capacity: 20°C-25°C below ambient temperature LCD display indicated the temperature inside; Attractive performance design,Suitable for wine or champagne bottle with diameter up to 90mm CPU constant temperature control; Fahrenheit rechargeable battery; Using thermoelectric peltier module,no compressor; Built-in rechargeable battery and charger version is optional for option Package: each in a color gift box: 22.5×21×30.5cm. 5pcs per carton(size:106.5×24×32.5cm) 1645pcs per 20'GP; 3465pcs per40'GP; 3960pcs per 40'HQ	NINGBO	1000	US\$24.15	35days