





YINGKOU SHENGDA MACHINE CO.,LTD.








ADD: Xishi Industrial Zone, Yingkou, Liaoning, China www.yksdq.com

Email: jim@yksdq.com Email: shengdaqb@163.com Skype: jimxuwan

TEL: +86-417-2259909 WeChat/WhatsApp: 008613840736626

NO.	FOB DALIAN	Picture	Specification Tire Vulcanizer
1	SD-CV08 USD65.		Technical parameters: Technical parameters: 220V Power: 800W Vulcanizing temperature: adjustable Operating pressure: 1.0-1.2MPa Applicable range: tube tire 400×200×500 8KG
2	SD-CV08B USD99.		Technical parameters: Technical parameters: 220V Power: 800W Vulcanizing temperature: adjustable Operating pressure: 1.0-1.2MPa Applicable range: tube tire 400×200×500 9KG
3	SD-CV18 USD156.		Supply voltage: 220V Power: 800W Vulcanizing temperature: adjustable Applicable range: tube tires and cover tires of small size tires 570x280x810 29KG
4	SD-CV18B USD210.		Supply voltage: 220V Power: 800W Vulcanizing temperature: adjustable Applicable range: tube tires and cover tires of small size tires 570x280x810 30KG

5	SD-CV88B USD285.		Supply voltage: 220V Power: 800W Vulcanizing temperature: auto controlled Applicable range: 750 to 10.00-20 tires. Control time 600x300x1150, 50KG
6	SD-CV88D USD310.		Supply voltage: 220V Power: 800W Vulcanizing temperature: auto controlled Control time Applicable range: 750 to 10.00-20 tires. 600x300x1150, , 60KG
7	SD-CV20 USD176.		Technical parameter: Supply voltage 220V Power 800W Vulcanizing temperature automatic control 620×135×350 , 13KG
8	SD-CV20B USD180.		Technical parameter: Supply voltage 220V Power 800W Vulcanizing temperature automatic control 620×135×350, 12KG
9	SD-CV900 USD275.		Technical parameters: Supply voltage: 220V Power: 800W Vulcanizing temperature: auto controlled 580x140x800 35KG

10	SD-1200-1 USD1000.		Supply voltage: 220V/380V Power: 5.4 KW Thermo-compression area: a quarter area of tires Vulcanizing temperature: 135-145°C Applicable range: 7.50-12.00 tires 940x940x900, 290KG
11	SD-1200-2 USD1,320.		Supply voltage: 220V/380V Power: 7KW Thermo-compression area: a quarter area of tires Vulcanizing temperature: 135-145°C Applicable range: 9.00-12.00 tires 1090x880x930, 375KG
12	SD-1500 USD3,885.	3 	Supply voltage: 220V/380V Power: 12KW Thermo-compression area: a quarter area of tires Vulcanizing temperature: 135-145°C Applicable range: 20.5-25 tires 23.5-25 tires 1510×1510×1280, 936KG
13	SD-1500-2 USD8,200.		Supply voltage: 380V Power: 17KW Weight of complete machine: 1T Vulcanizing temperature: adjustable Operating air pressure: 0.35-0.5Mpa Applicable tires: special for 24.00-35 mine truck tires.

Tire Spreader :

NO.	FOB DALIAN	Picture	Tyre Expander Specification
1	SD-TS2 USD156.		Technical parameter: Applicable scope for small tire 540x380x1080 41KG
2	SD-52C USD168.		Air cylinder. Technical parameter: Working pressure 0.8-1.0MPa For tire width below 1,200 600x600x1020 50KG
3	SD-62C USD586.		Technical parameter: Working pressure 0.8-1.0MPa For tire width below 1,200-20 large and medium-sized tire 1250x850x740 160KG
4	SD-TKA100 Car Tire Test Tanks USD550.		Efficient, safe and convenient testing of car, The mobile lift which can lift pallets up to 100 kg can be detached from the test tank.
5	SD-TK280 Truck Tire Test Tanks USD896.		Efficient, safe and convenient testing of car, truck, tractor and EM tubeless tyres as well as inner tubes. The mobile lift which can lift pallets up to 280 kg can be detached from the test tank. Dimensions: 1500x1600x1900mm