















Cangzhou Jiangcheng Machinery Co.,Ltd Product Catalogue

Product name	Model	Picture	Description	N.W/G.W	Package	packing size	war	MOQ
Hydraulic puller	JC-5T		working pressure:5T Axis effective extension:50mm Longitudinal Max. pull:140mm Lateral max. outside diameter:200mm	6.5/7.5KG	1pcs/Plastic Case 3pcs/Carton	46*30*33cm	6months	35
	JC-10T		working pressure:10T Axis effective extension:60mm Longitudinal Max. pull:160mm Lateral max. outside diameter:250mm	10.2/11KG	1pcs/Plastic case 3pcs/Carton	46*30*33cm	6months	35
Jack Stand	JS-3		Rated Load:3T max height:440mm min height:260mm Color:Red or yellow or customized Material:45# Steel	4.96/5.3KG	1pair/Carton	21.5*20.5*33.2cm	6months	100

Jack Stand	JS-6		Rated Load:6T max height:610mm min height:390mm Color:Red or yellow or customized Material:45# Steel	8.74/9.6KG	1pair/Carton	29.3*24.8*42.7cm	6months	100
Plastic Creeper	PC-40		Size: 40" Color:Red or yellow or customized Material: Polyvinyl chloride Wheel: Six Universal wheels	4.5 /5.5KG	1pcs/Carton 5cartons/Woven bag	104*9.8*44cm/ Carton 104*49*44cm/ Woven bag	6months	100
cylinder liner puller	YL-5		Working pressure:5T Working stroke:50mm Application range: Dry type cylinder liner inner diameter range 80-135mm	(37/38kg)/carton	1pcs/plastic case 2pcs/Carton	53*31*11cm/ plastic case 54*24*32cm/ carton	6months	20
	YL-10		Working pressure:10T Working stroke:60mm Application range: Dry type cylinder liner inner diameter range 80-135mm	(44/45kg)/carton	1pcs/plastic case 2pcs/Carton	53*31*11cm/ plastic case 54*24*32cm/ carton	6months	20





Pneumatic Oil Extractor	YY-1008		Capacity:80L Exhaust gas pressure:<0.8MP Tank capacity: 20 GAL Collect tray capacity:2.6 GAL Maximum height:160cm minimum height:100cm Gas pressure suction:4Mpa Put the tubing length:150cm Dimension of prodcut:57x38x100 cm	18.5/19.5KG	1pcs/carton	43*46*89cm	6months	30
	YY-3397		Capacity:80L Exhaust gas pressure:<0.8MP Tank capacity: 20 GAL Collect tray capacity:2.6 GAL Maximum height:160cm minimum height:100cm Gas pressure suction:4Mpa Put the tubing length:150cm Dimension of prodcut:57x38x100 cm	16.8/19KG 5.5/6.5KG	1/2 pcs/carton	43*46*89cm / 39*28*27cm	6months	30
	YY-3197		Capacity:80L Exhaust gas pressure:<0.8MP Tank capacity: 20 GAL Collect tray capacity:2.6 GAL Maximum height:160cm minimum height:100cm Gas pressure suction:4Mpa Put the tubing length:150cm Dimension of prodcut:57x38x100 cm	16.8/19KG 5.5/6.5KG	1/2 pcs/carton	43*46*89CM / 39*28*27cm	6months	30

Engine support bar	PHJ-1.8		length: 1.8m color: red	(17/18kg)/Piece (34/36kg)/carton	2pcs/Carton	183*17*18cm/ca	6months	50
	PHJ-1.5		length: 1.5m color: red	(15/16kg)/piece (30/32kg)/carton	2pcs/Carton	153*17*18cm/ca	6months	50
Engine Crane (Foldable)	ZD-2LA		Rated load: 2T Lifting Max. height:2300mm Lifting Min. height: 300mm Wheel: Six Universal wheels foldable:yes	65/67KG	1/2Pcs/carton	(1)142*30.5*18.5 cm (2)73*56*15cm	6months	30
	ZD-2HA		Rated load: 2T Lifting Max. height:2300mm Lifting Min. height: 300mm Wheel: Six Universal wheels foldable:yes	75/78KG	1/2Pcs/carton	(1)142*30.5*18.5 cm (2)73*56*15cm	6months	30




Engine Crane (Foldable)	ZD-2HB		Rated load: 2T Lifting Max. height:2300mm Lifting Min. height: 300mm Wheel: Six Universal wheels foldable:yes	81/85KG	1/2Pcs/carton	(1)142*30.5*18.5 cm (2)73*56*15cm	6months	30
	ZD-3H		Rated load: 3T Lifting Max. height:2400mm Lifting Min. height: 300mm Cylinder:16T Wheel: Six Universal wheels foldable:yes	115/140KG	1/2Pcs/carton	(1)180*35*23C M (2)83*90*17CM	6months	30
Engine Crane (Fixed)	GD-2L		Rated load: 2T Lifting Max. height:2300mm Lifting Min. height: 300mm Wheel: Four Universal wheels foldable:no	55/60KG	1/2Pcs/carton	(1)120*70*78C M (2)129*24*18C M	6months	30
	GD-3L		Rated load: 3T Lifting Max. height:2450mm Lifting Min. height: 500mm Cylinder:12T Wheel: Four Universal wheels foldable:no	105/115KG	1/2Pcs/wooden 2/2Pcs/wooven bag	(1)148*34.5*22 CM (2)132*91*11C M	6months	30

Engine Crane (Fixed)	GD-3H		<p>Rated load: 3T Lifting Max. height:2450mm Lifting Min. height: 500mm Cylinder:16T Wheel: Four Universal wheels foldable:no</p>	115/125KG	1/2Pcs/wooden 2/2Pcs/wooven bag	(1)148*34.5*22 CM (2)132*91*11C M	6months	30
Engine Crane (Euro style)	ZD-1E		<p>Rated load: 1T Max. height:1980mm Min. height: 0mm Wheel: Six Universal wheels foldable:yes</p>	76/78KG	1/2Pcs/carton	(1)136*28*18C M (2)75*58*8CM	6months	30
	ZD-2E		<p>Rated load: 2T Max. height:2180mm Min. height: 0mm Wheel: Six Universal wheels foldable:yes</p>	94/96KG	1/2Pcs/carton	(1)136*28*18C M (2)75*58*9CM	6months	30
Spring compressor	THJ-2(long arm)		<p>1、 Detachable spring Max diameter:200mm 2、 Detachable spring maximum height:500mm</p>	27/28KG	1pcs/kraft bag	40*33*87cm	6months	30

Spring compressor	THJ-3(high-grade)		<p>1、 Detachable spring Max diameter:200mm</p> <p>2、 Detachable spring maximum height:430mm</p>	30.5/32KG	1pcs/carton	67*35*21cm	6months	30
	YTH-01		<p>Jack cylinder piston stroke: 320mm</p> <p>Jack cylinder piston diameter: 28mm</p> <p>Minimum lifting height: 495mm</p> <p>Maximum lifting height:820mm</p> <p>Disassembly spring size:4"-10"</p>	27.5/29KG	1set/carton	107*26*21cm	6months	30
	YTH-02		<p>Jack cylinder piston stroke: 320mm</p> <p>Jack cylinder piston diameter: 28mm</p> <p>Minimum lifting height: 495mm</p> <p>Maximum lifting height:820mm</p> <p>Disassembly spring size:4"-10"</p>	27.5/29KG	1set/carton	107*26*21cm	6months	30
tire bead seater	JC8001 A1		<p>capacity:5 gallon</p> <p>color:yellow or black or customized</p> <p>certification:CE</p> <p>tank wall thickness:3.25mm</p> <p>Max.pressure:0.8Mp</p> <p>ball vale size:1.5 inch</p>	11.8/13.3KG	1 pcs/pvc bag/bubble 1pcs/carton	47*40*32.5cm	6months	100

tire bead seater	JC8001 A2		capacity:7.5 gallon color:yellow or black or customized certification:CE tank wall thickness:3.25mm Max.pressure:0.8Mp ball vale size:1.5 inch	12.1/13.5KG	1 pcs/pvc bag/bubble 1pcs/carton	46*39.5*34cm	6months	100
	JC8001 A3		capacity:10 gallon color:yellow or black or customized certification:CE tank wall thickness:3.25mm Max.pressure:0.8Mp ball vale size:1.5 inch	14.2/16.5KG	1 pcs/pvc bag/bubble 1pcs/carton	58.5*42*35cm	6months	100
	JC8001B1 (fast)		capacity:5 fast gallon color:yellow or black or customized certification:CE tank wall thickness:3.25mm Max.pressure:0.8Mp ball vale size:1.5 inch	12.75/14.5KG	1 pcs/pvc bag/bubble 1pcs/carton	67*39*34cm	6months	100
	JC8001B2 (fast)		capacity: 2 fast gallon color: any color customized certification:CE Max.pressure:0.8Mp tank length: 390mm diameter:16.5cm	6.2/6.8kg	1 pcs/pvc bag/bubble 1pcs/carton	57*18*22cm	6months	100

Vulcanizing machine	SH-D		<p>Working voltage:220V Rated power:2*500W Temperature range:150-180℃ Timer range:0-180 mins style:pneumatic type Using atmospheric pressure:6-8kg/cm2 product size:490*380*1700mm Repairing area:80*80mm car tires molds quantity: 8 piece Max current:8A</p>	45 / 46KG	1pcs/carton	64*56*110CM	6months	10
	XZ-D		<p>Working voltage:220V Rated power:2*500W Temperature range:150-180℃ Style:rotatable type product size:530*340*1330mm Applicable range:145 to 275 car tires molds quantity: 8 piece Max current:8A</p>	38 / 39KG	1pcs/carton	91*63*20CM	6months	10
	SH-18		<p>Working voltage:220V Rated power:2*500W Temperature range:150-180℃ Timer range:0-180 mins product size:350*100*660mm Applicable range:truck tires molds quantity: 7 piece Max current:8A</p>	23 / 24KG	1pcs/carton	69*38.5*18.5CM	6months	10


Vulcanizing machine	CX-D		<p>Working voltage:220V Rated power:2*500W Temperature range:0-400℃ Timer range:0-180 mins product size:520*220*67mm Applicable range:145 to 275 car tires molds quantity: 3 piece Max current:8A</p>	18.5 / 19.5kg	2pcs/carton	51*25.5*70.5CM	6months	20
	SH-12		<p>Working voltage:220V Rated power:2*500W Temperature range:150-180℃ Timer range:0-180 mins product size:530*280*80mm Applicable range:145 to 275 car tires tires molds quantity: 8 piece Max current:8A</p>	11.5/12.5kg	1pcs/carton	66*12*30CM	6months	20
	TD-28		<p>Working voltage:220V Rated power:2*500W Temperature range:150-180℃ N.W/G.W:9.8/10.8kg product size:530*280*80mm Applicable range:145 to 275 car tires molds quantity: 8 piece Max current:8A</p>	9.8/10.8KG	3pcs/carton	66*12*30cm	6months	30

Vulcanizing machine	LH-6		workig voltage: 220V rated power: 500W Temperature range:150-180℃ N.W/G.W: 5 / 6kg Product size: 280*240*400mm Applicable range: Inner tire molds quantity: 1 piece	5/6KG	1pcs/carton	29*27*41cm	6months	50
	DS-125		workig voltage: 220V rated power: 500W Temperature range:150-180℃ timer range:0-180mins N.W/G.W: 6.3 / 7kg Product size: 320*180*430mm Applicable range: Inner tire molds quantity: 1piece	6.3/7KG	1pcs/carton	32*19*44ccm	6months	50
	FM-125		workig voltage: 220V rated power: 400W Temperature range:150-180℃ N.W/G.W: 6 / 7kg Product size: 320*180*430mm Applicable range: Inner tire molds quantity: 1piece	6/7KG	1pcs/carton	33*19*44cm	6months	50
Auto heavy duty repairing tool torque wrench	JC-I KA		Voltage:380V Power:3.0KW Max torque:800NM Output speed:24 revolutions/min Product size:205*40*50CM	150/160KG	1pcs/wooden case	235*39*48cm	6months	5




Auto heavy duty repairing tool torque wrench	JC-II KA		Voltage:380V Power:4.0KW Max torque:2000NM Output speed:24 revolutions/min Product size:208*45*55CM	130/140KG	1pcs/wooden case	232*34*45cm	6months	5
	JC-III KA		Voltage:380V Power:4.0KW Max torque:2013NM Output speed:12revolutions/min Product size:188*42*50CM	105/115KG	1pcs/wooden case	192*34*45cm	6months	5
	JC-IV KA		Voltage:380V Power:4.0KW Max torque:2278NM Output speed:13revolutions/min Product size:228*45*55CM	135/150KG	1pcs/wooden case	232*34*45cm	6months	5
	JC-V KA		Voltage:380V Power:5.5KW Max torque:2585NM Output speed:14revolutions/min Product size:239*45*55CM	95/105KG	1pcs/wooden case	192*34*45cm	6months	5
	JC-880-A		Voltage:380V Power:4.0KW Max torque:2358NM Output speed: 7 revolutions/min Product size:205*40*50CM	120/130KG	1pcs/wooden case	192*34*45cm	6months	5


Transmission Jack	GW-0.5T		Rated load:0.5T Max height:1800mm Max height:830mm	43/46KG	1pcs/carton	75*42*24cm	6months	20
	GW-0.6T		Rated load:0.6T Max height:1860mm Max height:870mm Cylinder size:19.5 * 15 * 75cm	50/52KG	1pcs/carton	75*42*24cm	6months	20
	GW-1T		Rated load:1T Max height:1900mm Max height:1000mm	85/88KG	1pcs/wooden case	55*41*89cm	6months	10
	DW-2T A		Rated load:2T Max height:890mm Min height:230mm	77/84KG	1pcs/wooden	99*58.5*20cm	6months	10

Floor Transmission Jack	DW-2T B		Rated load:2T Max height:900mm Min height:190mm	55/57KG	1pcs/woven bag	65*110*25cm	6months	10
	DW-3T A		Rated load:3T Max height:905mm Min height:195mm	110/123KG	1pcs/wooden	116*68.5*32cm	6months	10
	DW-3T B		Rated load:3T Max height:905mm Min height:195mm	85/90KG	1pcs/woven bag	116*68.5*32cm	6months	10
Pneumatic Valve Grinder	QM-20B		Grinding valve max. weight:0.5KG Working pressure:3-6kg/cm ³ Working stroke:11-15mm Effective frequency:300-1100times/min Working speed:10-40Rev / min Gas consumption:0.28m ³ /min	1.2kg	1pc/plastic bags 10pcs/carton	43*24*33CM	6months	no stock

co2 mag welding machine	YY-270		<p>Input voltage phase:380v Frequency:50HZ Rated Max. input current:6.5kva Output current voltage:35A/17V-270A/28V No-load voltage:20-36v Welding current:35-270kva Temporary load rate:35% Insulation grade:F</p>	95 / 105kg	1pcs/wooden case	72*48*78cm	1year	5
			<p>Unified corresponding wire diameter :Low carbon steel solid wire 0.8/1.0 Series of voltage regulation:10. Wire feeding speed:2-25m/min wire diameter:0.8-1.0mm</p>			72*48*78cm and 53*24*40cm		
	YY-350		<p>Input voltage phase:380v Frequency:50HZ Rated Max. input current:9.3kva Output current voltage:35A/17V-350A/28V No-load voltage:20-45v Welding current:35-350kva Temporary load rate:35% Insulation grade:F</p>	116 / 126.5kg	1pcs/wooden case	72*48*78cm	1year	5
			<p>Unified corresponding wire diameter :Low carbon steel solid wire 1.0 /1.2 Series of voltage regulation:10. Wire feeding speed:2-25m/min wire diameter:0.8-1.0mm</p>			72*48*78cm and 53*24*40cm		


spot welding machine	YY-13000		<p>Input voltage: 110 /220V Frequency :50/HZ Output voltage: 4.5V Maximum output current:1300A Adjustable time: 0-3S power: 800W</p>	10/11KG	1pcs/carton	48.5*20*47cm	1year	10
	YY-16000		<p>input voltage:2PH 220V/380V frequency:50HZ/60HZ rated capacity:4.5KVA second welding current:200-6900A instant output power:18KVA duty cycle:15% automatic working time:0.1-1s work way:electronic timing continuity Welding Thickness:0.8-1.2mm Working gear:ABC Power:21KVA</p>	53kg/56kg	1pcs/wooden case	64*43*85cm	1year	5
	YY-18000		<p>input voltage:2PH 220V/380V frequency:50HZ/60HZ second welding current:200-8500A instant output power:23KVA duty cycle:15% automatic working time:0.1-1s work way:electronic timing continuity Welding Thickness:0.8-1.2mm Working gear:ABC Power:23KVA</p>	55kg/58kg	1pcs/wooden case	62.5*42*89cm	1year	5




spot welding machine	YY-21000		input voltage:2PH 220V/380V frequency:50HZ/60HZ rated capacity:5KVA second welding current:200-8500A instant output power:25KVA duty cycle:15% automatic working time:0.1-1s work way:electronic timing continuity Welding Thickness:0.8-1.2mm Working gear:ABC	78kg/80kg	1pcs/wooden case	96*63*46cm	1year	5
	YY-25000		input voltage:2PH 220V/380V frequency:50HZ/60HZ rated capacity:5KVA floating voltage:11.5V second welding current:200-8500A instant output power:25KVA duty cycle:15% automatic working time:0.1-1s work way:electronic timing continuity Welding Thickness:0.8-1.2mm Rated Duty Cycle:60% Working gear:1-99	78kg/80kg	1pcs/wooden case	96*63*46cm	1year	5
Tire mount/demount tool	Ordinary type		Material:steel packing size:30*30*150cm tyre size:heavy duty tyres tool:3pcs kit	7.3/7.8kg	1kit/kraft bag	30*30*150cm	1months	100

Tire mount/demount tool	Thickening type		Material:steel packing size:30*30*150cm tyre size:heavy duty tyres tool:3pcs kit	8.92/9.5kg	1kit/kraft bag	30*30*150cm	1months	100
	welding		Material:steel packing size:30*30*135cm tyre size:heavy duty tyres tool:3pcs kit	10.5/11kg	1kit/kraft bag	30*30*135cm	6months	50
	Separable		Material:steel packing size:100*27.5*24.5cm tyre size:heavy duty tyres tool:3pcs /kit	13.84/15kg	1kit/carton	100*27.5*24.5cm	6months	30
Vacuum tire changer			Motor power: 1850W/4000W Voltage:220V/380V Removable tires: disassembly 13R 22.5, 12R 22.5, 11R 22.5. Rotation speed: 15 seconds / lap	130/142.5kg	1set/wooden	93*50*48CM	6months	5

Automatic Tire Spreader	JC-7		Input voltage:220V Working pressure:0.4-0.8MPa Spreading width:75-380mm Spreading diameter:<=1200mm Spreading Capacity:1500KG	60KG	1pcs/carton	63*55*97cm	1year	10
Tire impact bar	IB-2		Length:1.2m(precision forging) Material:steel	10.5KG	5 pieces/Kraft paper bag	122*18*12cm	1months	50
	IB-4		Length:1.3m (precision forging) Material:steel	11.5KG	5 pieces/Kraft paper bag	132*18*12cm	1months	50
	IB-5		Length:1.2m (heavier,precision forging) Material:steel	12.5KG	5 pieces/Kraft paper bag	122*17*10cm	1months	50

tire layering extractor	YTQC-1		Length:1.18m Hook thickness: 1.9cm Material: cast steel	6.4KG/piece	10pcs/carton	124*15*16cm	3months	50
	YTQC-2		Length:1.05m Hook thickness: 1.8cm Material: cast steel	4.9KG/piece	10pcs/carton	124*15*16cm	3months	50
Oil Drain Pan	YP-10		Material : Polyethylene Diameter: 14.6" High:5.4" Capacity:10	4.47KG /6KG	6pcs/carton	45*44*60CM	3months	300
	YP-15		aterial : Polyethylene Diameter: 17.72" High:6.1" Capacity:15L	5.08KG /6.6KG	5pcs/carton	48*51*65CM	3months	300


tool cabinet	KH01		One drawer tool cabinet material:steel Steel thickness:1.0mm drawer size:575*400*140mm Rear wheels with brake	40kg/55kg	1piece/wooden	78x54.5x81cm	6months	10
	KH02		Two drawer tool cabinet material:steel Steel thickness:1.0mm small drawer size:575*400*620mm big drawer size:575*400*140mm Rear wheels with brake	44kg/59kg	1piece/wooden	78x54.5x82cm	6months	10
	KH03		Three drawer tool cabinet material:steel Steel thickness:1.0mm small drawer size:575*400*620mm big drawer size:575*400*140mm Rear wheels with brake	40kg/55kg	1piece/wooden	78x54.5x83cm	6months	10
	KH04		Four drawer tool cabinet material:steel Steel thickness:1.0mm small drawer size:575*400*620mm big drawer size:575*400*140mm Rear wheels with brake	40kg/55kg	1piece/wooden	78x54.5x84cm	6months	10

tool cabinet	KH05		Five drawer tool cabinet material:steel Steel thickness:1.0mm small drawer size:575*400*620mm big drawer size:575*400*140mm Rear wheels with brake	51kg/64kg	1piece/wooden	78x54.5x85cm	6months	10
	KH07		Seven drawer tool cabinet material:steel Steel thickness:1.0mm small drawer size:575*400*620mm big drawer size:575*400*140mm Rear wheels with brake	60kg/75kg	1piece/wooden	78x54x89cm	6months	10
	KYC-oo8		Seven drawer tool cabinet material:steel Steel thickness:1.2mm small drawer size:550*380*55mm big drawer size:550*380*130mm Product size with wheel s:68*47*99cm Rear wheels with brake	53/55kg	1piece/carton	71.5*50*90cm	6months	10
Wind Gun Mobile Crane	JC-LS2		Machine width: 50cm Machine height: 98cm lifting weight:25kg	75KG/95KG	1set/wooden		3months	10

Tire Changer Machine	L-988		<p>Power Supply: 220v/380v Motor Power:220v/1100w,380v/750w Outside Clamping:10"-22" Inside Clamping: 12"-24" Max.Wheel Width: 12.5"/315mm Bead -Breaker Force :2500kgf Operating Pressure: 6-8 Bar</p>	N.W.187KG	wooden case	1190*910*940mm	1 year	5
Wheel balancer	LB-139		<p>Voltage: 220v Screw shaft diameter:40mm Balancing speed:100rpm balance quality:1g Hub width range:1.5"-2.0" Hub dia.:8"-28" aut</p>	N.W.98KG	wooden case	1190*910*940mm	1 year	5
Shop Press Machine	YL20TL		<p>Related Load :20T Material : Steel Color: Customized Width : 55.5cm Height: 140 cm</p>	N.W 44KG	wooden case	142*20*11.5cm	1 year	20
coil spring compressor			<p>Heavy duty car coil spring compressor clamp 2pcs</p>	1.85kg/carton	1pair/Carton	385*85*60mm	6months	500

Roll Fender Reforming			Applicable models: Car and light truck	6.7kg/7.3kg	1 set/Carton	45*28.5*14.5cm	6months	50
Jack	Jc-3TKS		Rated capacity: ≤3T Min height:125mm Max height:480mm	30KG/31.72KG	1 set/Carton	76*37*21.5CM	6months	30
	JC-3TCD		Rated capacity: ≤3T Min height:75mm Max height:510mm	31KG/32.58KG	1 set/Carton	72.5*37*22.5cm	6months	30
	JC-3TWS		Rated capacity: ≤3T Min height:125mm Max height:490mm	26.5/28KG	1 set/Carton	67*34*18cm	6months	30

Hydraulic Porta Power Jack	JC-10T		Carrying capacity:10T Min height:322mm Stroke:130mm	29.5/30.5KG	1 set/Carton	42*18.5*73.5cm	6months	30
Airbag jack	JC-3Y		Capacity:3T Min height:14.5cm Max height:42cm Operating temperature:-30°C-+50°C	17.5kg/18.6kg	1set/carton	49*52*18.5cm	6months	
	JC-3F		Capacity:3T Min height:13.5cm Max height:41cm Operating temperature:-30°C-+50°C	15.6kg/16.7kg	1set/carton	49*52*18.5cm	6months	
	JC-4.5T		Capacity:5T Min height:15cm Max height:45cm Operating temperature:-30°C-+50°C	20KG/21.5KG	1set/carton	49*54*18.5cm	6months	

Manual demount kit			Type:hand Tool Material:steel Color:red with black Tool:6pcs/kit	55/67kg	1set/wooden	109*49*37cm	6months	
-----------------------	--	---	---	---------	-------------	-------------	---------	--

