



Specifications -SUBWOOFER

Photo	Brand/ Model	English Name&Description
	INF-21	<p>Type: Triple 21" Large format cardioid subwoofer</p> <p>1) Components: 2 x 21" front + 1 x 21" rear (VC: 152.4 mm ; Mag: 330.25 mm)</p> <p>2) Frequency Response: 27Hz - 90Hz(±3dB) 3) Sensitivity(1W/1M): 106dB 4) Maximum Peak SPL: 144dB(Front); 141 dB(Rear) 5) Rated Power(RMS): 2400W(Front); 1200W (Rear) 6) Peak Power(RMS): 9600W(Front); 4800W (Rear) 7) Impedance(Ohm): 4 ohm(Front); 8 ohm (Rear) 8) Connectors:1xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 685 x 1180 x 1040 mm 12) Net. W.: 150 kg</p>
	TSW-218	<p>Type: Dual 18" Line Array Subwoofer</p> <p>1) Components: 2X18" (Fe) 2) Frequency Response: 30Hz - 250Hz(±3dB) 3) Sensitivity(1W/1M): 102dB 4) Maximum Peak SPL: 136dB 5) Rated Power(RMS): 2400W 6) Peak Power(RMS): 4800W 7) Impedance(Ohm): 4 ohms 8) Connectors:2xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 1400*770*574 mm 12) Net. W.: 89 kg</p>
	VT4880	<p>Type: Dual 18" Line Array Subwoofer</p> <p>1) Components: 2X18" (Fe) 2) Frequency Response: 30Hz - 250Hz(±3dB) 3) Sensitivity(1W/1M): 102dB 4) Maximum Peak SPL: 134dB 5) Rated Power(RMS): 1800W 6) Peak Power(RMS): 3600W 7) Impedance(Ohm): 4 ohms 8) Connectors:2xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 493*1214*860 mm 12) Net. W.: 90 kg</p>

	<p>LA-218</p>	<p>Type: Dual 18" Line Array Subwoofer</p> <ol style="list-style-type: none"> 1) Components: 2x18" Subwoofer (Fe) 2) Frequency Response: 30Hz–250Hz(±3dB) 3) Sensitivity(1W/1M): 102 dB 4) Maximum Peak SPL: 134dB 5) Rated Power(RMS): 1800W 6) Peak Power(RMS): 3600W 7) Impedance(Ohm): 4 Ohm 8) Connectors:2xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 1160*921*580 mm 12) Net. W.: 98 kg
	<p>PH-218</p>	<p>Type: Dual 18" Line Array Subwoofer</p> <ol style="list-style-type: none"> 1) Components: 2X18" (Fe) - Italy Faital Pro 2) Frequency Response: 30Hz - 250Hz(±3dB) 3) Sensitivity(1W/1M): 102dB 4) Maximum Peak SPL: 136dB 5) Rated Power(RMS): 2400W 6) Peak Power(RMS): 4800W 7) Impedance(Ohm): 4 ohms 8) Connectors:2xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 1100*823*596 mm 12) Net. W.: 100 kg
	<p>SB1000Z</p>	<p>Type: Dual 18" Line Array Subwoofer</p> <ol style="list-style-type: none"> 1) Components: 2X18" (Fe) 2) Frequency Response: 38Hz - 250Hz(±3dB) 3) Sensitivity(1W/1M): 100dB 4) Maximum Peak SPL: 134dB 5) Rated Power(RMS): 1800W 6) Peak Power(RMS): 3600W 7) Impedance(Ohm): 4 ohms 8) Connectors:2xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 757*1072*538 mm 12) Net. W.: 85.5 kg
	<p>SB28</p>	<p>Type: Dual 18" Line Array Subwoofer</p> <ol style="list-style-type: none"> 1) Components: 2X18" (Fe) 2) Frequency Response: 30Hz-250Hz(±3dB) 3) Sensitivity(1W/1M): 102dB 4) Maximum Peak SPL: 134dB(Rated) 5) Rated Power(RMS): 1800W 6) Peak Power(RMS): 3600W 7) Impedance(Ohm): 4 Ohm 8) Connectors:1xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 1300*700*550 mm 12) Net. W.: 90 kg

	<p>PG-218</p>	<p>Type: Dual 18" Subwoofer 1) Components: 2X18" (Fe) 2) Frequency Response: 30Hz-250Hz(±3dB) 3) Sensitivity(1W/1M): 101dB 4) Maximum Peak SPL: 135dB(Rated) 5) Rated Power(RMS): 2000W 6) Peak Power(RMS): 4000W 7) Impedance(Ohm): 4 Ohm 8) Connectors:2xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 1065*744*561 mm 12) Net. W.: 87 kg</p>
	<p>PG-118</p>	<p>Type: Single 18" Subwoofer 1) Components: 1X18" (Fe) 2) Frequency Response: 40Hz-250Hz(±3dB) 3) Sensitivity(1W/1M): 98dB 4) Maximum Peak SPL: 125dB(Rated) 5) Rated Power(RMS): 800W 6) Peak Power(RMS): 1600W 7) Impedance(Ohm): 8 Ohm 8) Connectors:2xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 561*556*690 mm 12) Net. W.: 42 kg</p>
	<p>A-118</p>	<p>Type: Single 18" Subwoofer 1) Components: 1X18" (Fe) 2) Frequency Response: 33Hz-150Hz(±3dB) 3) Sensitivity(1W/1M): 102dB 4) Maximum Peak SPL: 128dB(Rated) 5) Rated Power(RMS): 900W 6) Peak Power(RMS): 1800W 7) Impedance(Ohm): 8 Ohm 8) Connectors:2xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 574*700*768 mm 12) Net. W.: 62 kg</p>
	<p>MG-118</p>	<p>Type: Single 18" Subwoofer 1) Components: 1X18" (Fe) 2) Frequency Response: 25Hz-170Hz(±3dB) 3) Sensitivity(1W/1M): 97dB 4) Maximum Peak SPL: 126dB(Rated) 5) Rated Power(RMS): 800W 6) Peak Power(RMS): 1600W 7) Impedance(Ohm): 8 Ohm 8) Connectors:2xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 660*660*560 mm 12) Net. W.: 40 kg</p>

	<p>MG-15</p>	<p>Type: Single 15" Subwoofer</p> <ol style="list-style-type: none"> 1) Components: 1X15" (Fe) 2) Frequency Response: 28Hz-170Hz(±3dB) 3) Sensitivity(1W/1M): 96dB 4) Maximum Peak SPL: 124dB(Rated) 5) Rated Power(RMS): 800W 6) Peak Power(RMS): 1600W 7) Impedance(Ohm): 8 Ohm 8) Connectors:2xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 500*600*600 mm 12) Net. W.: 36.7 kg
	<p>MG-12</p>	<p>Type: Single 12" Subwoofer</p> <ol style="list-style-type: none"> 1) Components: 1X12" (Fe) 2) Frequency Response: 39Hz-120Hz(±3dB) 3) Sensitivity(1W/1M): 98dB 4) Maximum Peak SPL: 123dB(Rated) 5) Rated Power(RMS): 600W 6) Peak Power(RMS): 1200W 7) Impedance(Ohm): 8 Ohm 8) Connectors:2xNL4 Speakon 9) Enclosure Material: High-strength Plywood 10) Cabinet Finish: Germany Water Paint 11) Dimensions (W*D*H): 565*500*395 mm 12) Net. W.: 24.8 kg